

YELLOW #13538 793-310

MSDS Number

BDDQG

National Stock Number

8010-00-162-7525

Product Name

YELLOW #13538 793-310

Manufacturer

AMERON INDUSTRIAL COATINGS DIV

Product Identification

Product ID:YELLOW #13538 793-310 MSDS Date:01/01/1985 FSC:8010 NIIN:00-162-7525 MSDS Number: BDDQG

Responsible Party

AMERON INDUSTRIAL COATINGS DIVISION

201 N BERRY ST

BREA, CA 92621-3904

US

Emergency Phone: 714-529-4597

Info Phone: 714-529-4597

Cage: 09869

Contractor

AMERON INDUSTRIAL COATINGS DIVISION

BREA, CA 92621-3904

714-529-4597

US

Cage: 09869

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6 RTECS: SE7555000

Fraction By Weight: 18%

OSHA PEL100 PPM

TOLUENE (SARA III)

CAS: 108-88-3 RTECS: XS5250000

Fraction By Weight: 0-10% OSHA PEL200 PPM/150 STEL ACGIH TLV: 50 PPM; 9293 EPA Report Quantity: 1000 LBS



DOT Report Quantity: 1000 LBS

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

Fraction By Weight: 14%

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

ISOBUTYL ACETATE (SARA III)

CAS: 110-19-0

RTECS: AI4025000

Fraction By Weight: 24%

OSHA PEL150 PPM

ACGIH TLV: 150 PPM; 9192 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000 Fraction By Weight:

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

Hazards

Effects of Overexposure: INHALATION: ANESTHETIC, IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

First Aid

First Aid:IN CASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST.

Fire Fighting

Flash Point:28FT.C.C

Lower Limits:.9

Extinguishing Media: USE CARBON DIOXIDE OR DRY CHEMICAL FOR SMALL FIRES. Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE DUE TO PRESSURE BUILD-UP.

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, AND ELECTRICAL, STATIC, OR FRIIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERTBSORBENT AND NON-SPARKING TOOLS.



Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGOF NFPA CLASS 1 FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions: DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO T FLAME CUT, BRAZE OR WELD COATED MATERIAL W/OUT RESPIRATOR.

Exposure Controls

Respiratory Protection: IN OUTDOOR OR OPEN AREAS USE APPROVED MECHANICAL FILTER.

Ventilation: PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION.

Protective Gloves: REQUIRED

Eye Protection: SPLASH-PROOF EYEWEAR

Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT TO

CONTAMINATED CLOTHING. Supplemental Safety and Health

604 E. 13TH STREET ANDOVER, KANSAS 67002

Chemical Properties

HCC:F2

Boiling Pt:B.P. Text:174-329F

Vapor Density:YES

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 78.1

Stability

Stability Indicator/Materials to Avoid:YES (MATERIALS TO AVOID)
Stability Condition to Avoid:AVOID FIRES, HEAT, AND HOT SURFACES.

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.