793716 LAC SPRAYING WHITE 17875

MSDS Number

BDDWF

National Stock Number

8010-00-165-6141

Product Name

793716 LAC SPRAYING WHITE 17875

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID:793716 LAC SPRAYING WHITE 17875 MSDS Date:01/01/1985 FSC:8010

NIIN:00-165-6141 MSDS Number: BDDWF

Responsible Party

PRATT AND LAMBERT INC

16116 E 13TH ST

WICHITA, KS 67201

US

Emergency Phone: 716-873-6000 DOT EMER 8002553924

Info Phone: 316-733-1361

Cage: 61196 **Contractor**

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902 Cage: 61196

Ingredients

ISOBUTYL ACETATE RTECS: NP9100000

Fraction By Weight: 25% ACGIH TLV: 150 PPM

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1 RTECS: NP9625000 Fraction By Weight: 8% OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293 EPA Report Quantity: 5000 LBS



DOT Report Quantity: 5000 LBS

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6 RTECS: SE7555000 Fraction By Weight: 15%

OSHA PEL100 PPM

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 15%

OSHA PEL200 PPM

ACGIH TLV: 200 PPM/300STEL;9394
EPA Report Quantity: 5000 LBS
DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000 Fraction By Weight:

OSHA PEL200 PPM/150 STEL
ACGIH TLV: 50 PPM; 9293
EPA Report Quantity: 1000 L

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:INHAL:ANEST,IRRIT OF RESPIR TRACT OR ACUT NERV SYS DEPRESN,HDACH,DIZZ,CONFUS,UNCONSCIOUS,COMA.

First Aid

First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOV TO FRESH AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST.

Fire Fighting

Flash Point: 21F TCC-6C

Lower Limits:.90

Extinguishing Media: USE FIRE EXTING(CO*2, DRY CHEM OR ALCOH FOAM) LO

FIRE-POLYMER

Fire Fighting Procedures: SELF-CONTAINED BREATH APPARATUS SHLD BE AVAIL

F/FIREMEN.

Unusual Fire/Explosion Hazard: KEEP CONTNRS TIGHTLY CLOS: ISOLAT FR HEAT, ELECTR EQPMT. SPARKS & OPEN FLAM. CLOS CONTNRS MAY EXPLO(SUP)

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION(FLAMES, HOT SURFACES, & ELECTRICAL, STATIC OR FRICTIONAL SPARKS) AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

Handling



Handling and Storage Precautions:DO NOT STORE AVOV 120F.STORE LG QUANTITIES IN BLDG DESINED TO COMPLY W/OSHA 1910.106.
Other Precautions:CONTNRS GROUNDED WHEN POURING.AVOID FRE FALL OF LIQD.IN EXCES OF FEW INCHS.DON'T FLAM CUT,BRAZ OR WELD COATED MATRL W/O BUR OF MNES APPRVD RESPIR OR APPROP VENT.AD LABL WARN"DO NOT TAK INTERNA

Exposure Controls

Respiratory Protection: OUTDOOR/OPEN AREAS, USE BUR. OF MINES APPRVD MECH

FILTR RESPIRATOR.

Ventilation: PROVID GEN DILUT OR LOC EXHAUST VENT IN VOL TO KEEP BELO

TLV

Protective Gloves:F/REPTD CONTACT Eye Protection:SAFETY EYEWEAR

Other Protective Equipment: PRMVT PROLONG SKIN CONTACT TO CONTAMINATED

CLOTHING

Supplemental Safety and Health

UNUS FIRE & EXPLOS HAZ: WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO

VERY HOT SURFACES.

Chemical Properties

HCC:F2

Boiling Pt:B.P. Text:174-290F

Vapor Density: HEAV

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume:80

Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:AVOID FIRES,HEAT & HOT SURFACES.

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE W/LOC,STATE & FEDERAL REGULATIONS INCINERATE IN APPRVD FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.