

## **OE-40 (MC 1093)**

### **MSDS Number**

BDHNNH

### **National Stock Number**

9150-00-188-9860

### **Product Name**

OE-40 (MC 1093)

### **Manufacturer**

IMPERIAL OIL CO INC

### **Product Identification**

Product ID:OE-40 (MC 1093)

MSDS Date:01/01/1985

FSC:9150

NIIN:00-188-9860

MSDS Number: BDHNNH

### **Responsible Party**

IMPERIAL OIL CO.,INC

Emergency Phone: (201) 591-9400

Cage: 58563

### **Contractor**

IMPERIAL OIL CO INC

279

MORGANVILLE, NJ 07751

US

732-591-8825

Cage: 58563

### **Ingredients**

PETROLEUM BASED LUBRICANTS(OIL)

Fraction By Weight: 100%

PROPRIETARY ADDITIVES - FOR MORE INFORMATION CALL CHEVRON

Fraction By Weight: 8-10%

### **Hazards**

Effects of Overexposure:NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO HEALTH.

### **First Aid**

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER.

INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.

### **Fire Fighting**

Flash Point:230C(446F)-(OC)

Extinguishing Media:CO\*2, FOAM, DRY CHEM & H\*2O FOG.

Fire Fighting Procedures:USE MESA/NIOSH APPRVD SCBA;USE H\*2O SPRAY TO COOL CONTNRS.

Unusual Fire/Explosion Hazard:NONE

### **Accidental Release**

Spill Release Procedures: DIKE & CONTAIN SPILL W/INERT MATERIAL(SAND,EARTH,FULLERS EARTH ETC.) TRANSFER LIQ TO DRUMS OR OTHER CONTAINERS FOR RECOVERY/DISPOSAL. AREA MAY BE SLIPPERY CARE SHOULD BE TAKEN TO AVOID FALLS. "PREVENT MATERIAL FROM GETTING INTO SEWERS/OPEN BODIES OF H<sup>2</sup>O".

## Handling

Handling and Storage Precautions: THESE LUBRICANTS BECOME VERY VISCOUS WHEN STORED AT LOW TEMPERATURES. THEY CONGEAL AT TEMPERATURES FROM -12 TO -32C.

## Exposure Controls

Ventilation: NORMAL ROOM VENTILATION.  
Protective Gloves: IMPERVIOUS  
Eye Protection: CHEM SPLASH GOGGLES  
Other Protective Equipment: EYEWASH FACILITY  
Supplemental Safety and Health  
SPEC REF: MIL-L-2104D; MFR SPECIFIED 6/22/84 THAT PRODUCT ALSO AVAILABLE IAW MIL-L-2104C, AMD 1 UNDER MIL SYMBOL: OE/HDO-40; SEE P/N IND A FOR DATA OF OE-40(MC 1115) IAW MIL-L-2104D; MSDS UNDATED.

## Chemical Properties

HCC: V6  
Boiling Pt: B.P. Text: >600F  
Vapor Pres: Vapor Density: Spec Gravity: Evaporation Rate & Reference: Solubility in Water: NEGLIGIBLE  
Appearance and Odor: DARK AMBER OIL, NO ODOR  
Percent Volatiles by Volume: 0

## Stability

Stability Indicator/Materials to Avoid: YES  
Stability Condition to Avoid: HEAT, IGNITION SOURCES  
Hazardous Decomposition Products: ONLY WHEN BURNING, GIVES CARBON MONOXIDE & CARBON DIOXIDE.

## Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.