

# **J-CIL SAE 10W MOTOR OIL**

# **MSDS Number**

**BDHWD** 

## **National Stock Number**

9150-00-191-2772

### **Product Name**

J-CIL SAE 10W MOTOR OIL

#### Manufacturer

E C MORRIS CORP

### **Product Identification**

Product ID:J-CIL SAE 10W MOTOR OIL MSDS Date:01/01/1987 FSC:9150 NIIN:00-191-2772 MSDS Number: BDHWD

MSDS Number: BDHWD

# **Responsible Party**

E. C. MORRIS CORPORATION

1205 BOWMAN STREET

WOOSTER, OH 44691

US

Emergency Phone: 216-264-1126

Info Phone: 216-264-1126

Cage: KO558

Contractor

MORRIS E C CORP

WADSWORTH, OH 44281

US

216-264-1126

Cage: 5X433

# **Ingredients**

>15G/KG),TAKE TLV AS
Fraction By Weight: 91.0%
ACGIH TLV: 5MG/CUM(OILMIST

DETERGENT INHIBITOR (CONTAINS ZINC DIALKYLDITHIOPHOSPHATE)

Fraction By Weight: 8.6% ACGIH TLV: NOT SPECIFIED

60.3GM/KG)

Fraction By Weight: 0.4% ACGIH TLV: NOT SPECIFIED

**Hazards** 



Effects of Overexposure: EYES & SKIN: IRRITATION; INGESTION/INHALATION: CHEMICAL PNEUMONITIS; DROWSINESS, HEADACHE, NAUSEA

#### First Aid

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H\*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

# **Fire Fighting**

Flash Point:410F/210C (C.O.C

Extinguishing Media:CO\*2,DRY CHEMICAL,FOAM OR WATER FOG.

Fire Fighting Procedures: NONE NOTED, MAY USE NIOSH/MSHA APPROVED SCBA IN

**ENCLOSED AREA** 

Unusual Fire/Explosion Hazard: WATER MAY CAUSE FROTHING.

#### **Accidental Release**

Spill Release Procedures: USE PROPER PERSONAL PROTECTION; USE SUITABLE DRY, INERT ABSORBENT MATERIALS AND RECOVER FOR PROPER DISPOSAL.

# Handling

Handling and Storage Precautions: STORE IN STEEL DRUM OR TANK BELOW 120F; KEEP AWAY FROM HEAT OR OPEN FLAMES. KEEP CONTAINER CLOSED WHEN NOT IN USE. HANDLE EMPTY CONTAINER CAREFULLY.

Other Precautions: AVOID CONTACT WITH SKIN AND EYES. DO NOT BREATHE

# **Exposure Controls**

VAPORS OR MIST.

Respiratory Protection: USE NIOSH/APPROVED RESPIRATOR FOR ORGANIC

VAPORS/MIST, IF ABOVE TLV

Ventilation: MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE

**VENTILATION** 

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY/CHEM GOGGLES

Other Protective Equipment: FULL PROTECTIVE CLOTHING, SAFETY SHOWER, EYE

WASH STATION

Supplemental Safety and Health

MSDS UNDATED: ITEM IS GRADE 10 OF SPEC MIL-L-2104

# **Chemical Properties**

HCC:V6

Boiling Pt:B.P. Text:700F/371C

Vapor Pres:>.1 Vapor Density:>1.0 Spec Gravity:0.88

Evaporation Rate & Reference:Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIGHT AMBER COLORED LIQUID-FAINT PETROLEUM ODOR

Percent Volatiles by Volume: NIL

### Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDANTS

Stability Condition to Avoid: HEAT, OPEN FLAMES

Hazardous Decomposition Products:CO,CO\*2,TRACE OXIDES OF S,ZN,P

### **Disposal**

Waste Disposal Methods: DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their





particular situation.

\_\_\_\_