

EPOXY EA 913, PART A

MSDS Number

BDKBL

National Stock Number

8010-00-222-9038

Product Name

EPOXY EA 913, PART A

Manufacturer

DEXTER CORP HYSOL DIV

Product Identification

Product ID:EPOXY EA 913, PART A

MSDS Date:01/01/1987

FSC:8010

NIIN:00-222-9038

MSDS Number: BDKBL

Responsible Party

DEXTER CORPORATION,HYSOL DIVISION

Emergency Phone: (415) 687-4201

Cage: 79436

Contractor

DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

312

BAY POINT, CA 94565-3299

US

202-483-7616

Cage: 33564

Ingredients

EPOXY RESINS

Fraction By Weight: 67.0%

ASBESTOS (AMIANTHUS, OBSOLETE AMOSITE), (FOR OSHA PEL, SEE

CAS: 1332-21-4

RTECS: CI6475000

Fraction By Weight: 32.0%

OSHA PEL0.2 FIBERS/CC

ACGIH TLV: 0.5 FIBERS/CC; A1;89

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

UNIDENTIFIED COMPONENTS

Fraction By Weight: 01.0%

Hazards

Effects of Overexposure:SKIN:IRRIT.POSS ALLRGC REACTION/SENSITIZATION;
EYES:CAUSES IRRITATION; INHAL/INGEST:NOT KNOWN

First Aid

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

Fire Fighting

Flash Point Method:TCC
Flash Point:>93.3C, 200.F
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL
CONTR.
Unusual Fire/Explosion Hazard:DENSE SMOKE MAY BE LIBERATED

Accidental Release

Spill Release Procedures:RMV IGN SOURCES.WEAR PROTECTIVE CLOTHING &
EQUIPMENTS.COVER WITH ABSORBENT MATL & SCRAPE UP.PLACE IN METAL
CONTAINER.WIPE UP REMAINING RESIDUE W/SOLVENTS OR WITH
DETERGENT.PLACE ALL RAGS & WASTE IN CO VERED METAL CONTAINER
PENDING DISPOSAL.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED
Other Precautions:AVOID CONTACT W/CLOTHING & SKIN.USE NIOSH APPROVED
MASK FOR DUSTS IF CURED PRODUCT IS TO BE DRY SANDED,ABRADED,ETC.

Exposure Controls

Respiratory Protection:NONE SHOULD BE NEEDED
Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE
VENTILATION
Protective Gloves:PLASTIC, LATEX
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING
Supplemental Safety and Health
MSDS FM MFR IS DATED:08/17/84.KEY1:N1.

Chemical Properties

HCC:V5
Spec Gravity:1.2
Solubility in Water:NEGLIGIBLE
Appearance and Odor:GREY PASTE WITH EPOXY ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS,STRONG LEWIS OR MINERAL ACIDS
Stability Condition to Avoid:NOT KNOWN
Hazardous Decomposition Products:CO,OXIDES OF
NITROGEN,ALDEHYDES,UNDETERMINED ORGANICS.
Conditions to Avoid Polymerization:AVOID MIXING RESIN & CURING AGENT IN
BATCHES MORE THAN 1LB

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF
IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.