

## **S.D. WOOD TURPENTINE**

### **MSDS Number**

BDNJV

### **National Stock Number**

8010-00-246-6442

### **Product Name**

S.D. WOOD TURPENTINE

### **Manufacturer**

NU BRITE CHEMICAL CO INC STERLING GROUP

### **Product Identification**

Product ID:S.D. WOOD TURPENTINE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-246-6442

MSDS Number: BDNJV

### **Responsible Party**

NU-BRITE CHEMICAL CO INC, STERLING GROUP

NINE OHIO RIVER BLVD

SEWICKLEY , PA 15143-2199

US

Emergency Phone: 800-424-9300

Info Phone: 412-766-7600

Cage: 78580

### **Contractor**

NU-BRITE CHEMICAL CO INC, STERLING GROUP

SEWICKLEY, PA 15143-2199

US

CHEMTREC 800-424-9300

Cage: 78580

### **Ingredients**

S.D. WOOD TURPENTINE

RTECS: VO8400000

Fraction By Weight: 100%

ACGIH TLV: 100PPM

### **Hazards**

Effects of Overexposure:SKIN:IRRIT, DERMAT,BURNS. EYE:IRRIT, DAMAGING,  
VAPOR IRRIT. INGEST:SERIOUS ILLNESS,DEATH-SUPP DATA

### **First Aid**

First Aid:EYE: FLUSH W/WATER FOR 15 MIN,CALL MD. SKIN: WASH W/SOAP &  
WATER,CALL MD IF NEC. REMOVE & WASH CONTAMINATED CLOTH. INH: REMOVE  
FROM EXPOS;CALL MD IF NEC. INGEST: CALL MD IMMED.GIVE EDIBLE  
OIL,STOMACH PUMP MAY BE NEC,ASPIRATION A HAZARD IF VOMITING.

### **Fire Fighting**

Flash Point:92F;33C, TCC

Lower Limits:0.8

Extinguishing Media: DRY CHEMICAL, CO<sub>2</sub>, FOAM, WATER MAY BE INEFFECTIVE.  
Fire Fighting Procedures: USE WATER TO COOL HEAT EXPOSED CONTAINERS  
Unusual Fire/Explosion Hazard: POSSIBLE EXPLOSION HAZARD DUE TO PRESSURE  
BUILD UP IN HEAT EXPOSED CONTAINERS.

## Accidental Release

Spill Release Procedures: AVOID INHAL OF VAPORS. REMOVE ANY POSS SOURCES  
OF IGNITION. VENTILATE AREA THOROUGHLY. MOP UP SPILL MATERIAL W/MOPS  
& RAGS, FOLLOWED BY WASHING W.DETERGENT & WATER.

## Handling

Handling and Storage Precautions: STORE & KEEP AWAY FROM ALL SOURCES OF  
HEAT & FLAME. STORE AWAY FROM STRONG OXIDIZING AGENTS & MATERIALS.  
CONTAINER: 1 PT CAN.

Other Precautions: GROUND CONTAINER WHEN POURING, FREE FALL OF LIQUID  
SHOULD NOT BE OVER A FEW INCHES. DO NOT INGEST. AVOID PROLONGED  
CONTACT W/SKIN. PRODUCT HAS BEEN DISCONTINUED. SPEC: TY 1 CL  
2-CANCELLED 7-79

## Exposure Controls

Respiratory Protection: NIOSH/MSHA APPROVED RESPIRATOR RECOMMENDED FOR  
EXPOSURE OF CONCERN.  
Ventilation: LOCAL EXHAUST & MECHANICAL RECOMMENDED TO KEEP BELOW TLV.  
Protective Gloves: RUBBER GLOVE REF  
Eye Protection: CHEM GOGGLES GLOVE REF  
Supplemental Safety and Health  
SYNONYM: SPIRITS OF TURPENTINE. OVEREXPOS: INH: HDACH, CHEST PAIN,  
NARCOSIS. OVEREXPOS & FIRST AID FROM GLOVE MSDS REFERENCE. VP VALUE IS  
FOR ALPHA PINE. SP GRAV VALUE IS AT 15.5C.

## Chemical Properties

HCC: F3  
Boiling Pt: B.P. Text: 311F; 155C  
Vapor Pres: 3.2  
Vapor Density: 4.84  
Spec Gravity: 0.862  
Evaporation Rate & Reference: 375 ETHER=1  
Solubility in Water: SLIGHT  
Appearance and Odor: CLEAR, WATER WHITE OILY LIQUID; AROMATIC ODOR  
Percent Volatiles by Volume: 100

## Stability

Stability Indicator/Materials to Avoid: YES  
STRONG OXIDIZING AGENTS, OXIDATION CATALYSTS- GLOVE MSDS REF.  
Hazardous Decomposition Products: CO<sub>2</sub>, CARBON MONOXIDE

## Disposal

Waste Disposal Methods: MFR RECOMMENDS REMOVING CONTAMINATED MOPS & RAGS  
TO DUMP AREA & DISPOSING OF BY BURNING THEM. DO NOT INCINERATE  
CLOSED CONTAINERS OF TURPENTINE. DISPOSAL METHOD MUST BE IAW  
FEDERAL, STATE & LOCAL CODE S.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.