

V-114 VULCABOND

MSDS Number

BDNKM

National Stock Number

8030-00-246-9925

Product Name

V-114 VULCABOND

Manufacturer

STANCHEM INC

Product Identification

Product ID:V-114 VULCABOND

MSDS Date:01/01/1985

FSC:8030

NIIN:00-246-9925

MSDS Number: BDNKM

Responsible Party

STANCHEM INC

401 BERLIN ST

EAST BERLIN , CT 06023-9706

US

Emergency Phone: 203-828-0571

Info Phone: 203-828-0571

Cage: 78520

Contractor

STANCHEM INC

EAST BERLIN, CT 06023-9706

US

203-828-0571

Cage: 78520

Ingredients

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 80%

OSHA PEL200 PPM

ACGIH TLV: 200 PPM/300STEL;9394

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PHENOL

CAS: 108-95-2

RTECS: SJ3325000

Fraction By Weight:

OSHA PELS, 5 PPM

ACGIH TLV: S, 5 PPM; 8990

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:LOCAL IRRITATION & NARCOSIS

First Aid

First Aid:REMOVE FROM EXPOSURE AREA. LOOSEN TIGHT CLOTHING. APPLY ARTIFICIAL RESP IF UNCONSCIOUS.

Fire Fighting

Flash Point:28F, -2C OC

Lower Limits:1.8

Upper Limits:11.5

Extinguishing Media:FOAM, CO2 OR DRY CHEMICAL

Fire Fighting Procedures:TREAT AS FLAMMABLE LIQUID IN WET STATE.

Accidental Release

Spill Release Procedures:HANDLE AS A FLAMMABLE LIQUID.

Handling

Handling and Storage Precautions:DO NOT STORE NEAR OXIDIZING MAT'LS OR HEATING EQUIPMENT

Other Precautions:STORE BELOW 90F

Exposure Controls

Respiratory Protection:EXTENDED EXP-RESPIRATOR W ACT. CHARCOAL FILTER OR IND. AIR SUPPLY

Ventilation:LOCAL IN SMALL AREAS; MECHANICAL ON LGE SURFACE APPLICATION.

Protective Gloves:POLYETHYLENE

Eye Protection:GLASSES/SIDE SHIELDS.

Supplemental Safety and Health

Chemical Properties

HCC:F2

Boiling Pt:B.P. Text:176F, 80C

Vapor Pres:71

Vapor Density:1.4

Spec Gravity:0.86

Evaporation Rate & Reference:4.6/ BUAC

Solubility in Water:MODERATE

Appearance and Odor:BLUE LIQUID W COMBINATION KETONE-PHENOLIC RESIN OD

Percent Volatiles by Volume:84

Stability

Stability Indicator/Materials to Avoid:YES

OXIDIZING MAT'LS

Disposal

Waste Disposal Methods:SOAK UP WET ADHESIVE ON AN ABSORBENT MAT'L, PLACE IN CLOSED CONTAINER & DISPOSE W SOLID WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.