

## **EN. EQUIP. LIGHT GRAY**

### **MSDS Number**

BDTQJ

### **National Stock Number**

8010-00-285-4869

### **Product Name**

EN. EQUIP. LIGHT GRAY

### **Manufacturer**

PRATT AND LAMBERT

### **Product Identification**

Product ID: EN. EQUIP. LIGHT GRAY

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00-285-4869

MSDS Number: BDTQJ

### **Responsible Party**

PRATT & LAMBERT

Emergency Phone: 316-733-1361

Cage: PRATT

### **Contractor**

PRATT AND LAMBERT INC

2153

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

### **Ingredients**

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 25%

ACGIH TLV: 500PPM

LEAD NAPHTHENATE 36%

RTECS: OG1945000

Fraction By Weight:

METHYL ETHYL KETOXIME

RTECS: PM7783000

Fraction By Weight:

TRIETHYLAMINE (SARA III)

CAS: 121-44-8

RTECS: YE0175000

Fraction By Weight:

OSHA PEL25 PPM/15 STEL

ACGIH TLV: 10 PPM/15 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

## Hazards

Effects of Overexposure:INHAL:ANEST. IRRIT OF NOSE,THROAT,EYES & POSS DIZZ.& NAUSEA.SPRA MISTS CONTN LEAD.PB POISN-HDACH,DIZ

## First Aid

First Aid:INHAL:REMOV FR EXPOSUR & PROVID FRESH AIR. SPLASH EYES:FLUSH IMMED.W/LG AMTS.OF WATR F/15 MIN. SPLASH SKIN-REMOV CONTAMINAT CLOTHNG & WASH ALL AFFECT AREA W/WATER. INGESTION:DO NOT INDUCE VOMITING.CALL A "DR" IMMED. IN ALL CASES.

## Fire Fighting

Flash Point:104F TCC 40C

Extinguishing Media:CARBON DIOXIDE, DRY CHEM, OR ALCOH FOAM.

Fire Fighting Procedures:SELF-CONTND BREATHING APPARAT SHLD BE AVAIL F/FIREMEN.

Unusual Fire/Explosion Hazard:KEEP CONTNRS TIGHTLY CLOS.ISOLAT FR HEAT,ELECT EQPMT,SPARKS & OPN FLAME.CLOS CONTNRS MAY EXPLOD (SUP

## Accidental Release

Spill Release Procedures:REMOV ALL SOURCES OF IGNIT (FLAMES,HOT SURFACES, & ELECTR, STATIC OR FRICTIONAL SPARKS).VENTILATE AREA & AVD BREATHING VAP. REMOV W/INERT ABSORBENT & NON-SPARKING TOOLS. STEPS MUST BE TAKEN TO PREVENT CONTAM OF GROUND WATER OR STREAMS.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG QTYS. IN COMPLIANCE W/OSHA 1910.106.CONTNRS SHLD BE GROUNDED & BONDED TO THE RECEIVING CONTAINER.

Other Precautions:DO NOT CUT OR WELD ON EMPTY CONTNR. "DO NOT USE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER."

## Exposure Controls

Respiratory Protection:USE NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY WHN SPRA OUTDR OR

Ventilation:PROVID GEN DILUT OR LOC EXHAUST VENT IN VOLM TO KEEP BELO AC

Protective Gloves:SOLVNT IMPERMEA

Eye Protection:SAFETY EYEWEAR

Other Protective Equipment:PROTECTIVE EQPMT TO PRVNT SKIN CONTCT.SEE 29,CFR 1910.1025

Supplemental Safety and Health

UNU. FIRE & EXPLOS. HAZ:WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO VERY HOT SURFACES.

## Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:311-373F

Vapor Density:HEAV

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:49

## Stability

Stability Indicator/Materials to Avoid:YES

AVD CONTCT W/STRONG ACIDS OR AKALINE MATERIALS.

Stability Condition to Avoid:FIRES, HEAT & HOT SURFACES.

Hazardous Decomposition Products:BURNING W/PRODUCE SMOKE & OXIDES OF CARBON & LEAD

Conditions to Avoid Polymerization:DO NOT ADD DRIERS OR REACTIV CHEMS

W/O TECHNICAL SUPERVISION

## **Disposal**

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL, STATE, & FED. REGULATIONS. INCINERATE IN EPA APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.