

## X-3796 TT-P-664 PRIMER COATING RED COMP L

#### **MSDS Number**

**BDVPP** 

## **National Stock Number**

8010-00-292-1127

### **Product Name**

X-3796 TT-P-664 PRIMER COATING RED COMP L

#### Manufacturer

SENTRY PAINT AND CHEMICAL CO

## **Product Identification**

Product ID:X-3796 TT-P-664 PRIMER COATING RED COMP L

MSDS Date:07/14/1988

FSC:8010 NIIN:00-292-1127 MSDS Number: BDVPP

# Responsible Party

SENTRY PAINT AND CHEMICAL CO

MILL AND LAWRENCE ST

DARBY, PA 19023

US

Emergency Phone: 215-522-1900

Info Phone: 215-522-1900

Cage: 34346

#### **Contractor**

SENTRY PAINT AND CHEMICAL CO

DARBY, PA 19023

\_ \_ \_ \_

US

Cage: 34346

## Ingredients

CHROMIUM (SARA III)

CAS: 7440-47-3

RTECS: GB4200000

Fraction By Weight: 1.35%

OSHA PEL1 MG/M3

ACGIH TLV: 0.5 MG/M3; 9192 EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

LEAD (SARA III)

CAS: 7439-92-1

RTECS: 0F7525000

Fraction By Weight: 0.37%

OSHA PEL0.05 MG/M3;1910.1025



ACGIH TLV: 0.15 MG/M3; DUST 9192

EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: E01400000

Fraction By Weight: 7.6%

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

TRIETHYLAMINE (SARA III)

CAS: 121-44-8

RTECS: YE0175000

Fraction By Weight:

OSHA PEL25 PPM/15 STEL

ACGIH TLV: 10 PPM/15 STEL; 9293 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000 Fraction By Weight:

OSHA PEL200 PPM/150 STEL ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

## **Hazards**

Effects of Overexposure: EYE: SEV IRRIT SKIN: DEFAT/DERM INH:DIZZ/WEAK/NAUS/UNCONS/ASPHYX ING:VOMIT/DIARR. IN LUNG:CHEM PNEUM.

## First Aid

First Aid:SKIN:WASH W/SOAP & WATER. REMOVE CONTAM CLTHNG. EYES:FLUSH W/WATER AT LEAST 15 MINS CALL MD. INH: MOVE TO FRESH AIR. GIVE O\*2, ART RESP AS NEC. KEEP WARM/QUIET CALL MD. ING: DO NOT INDUCE VOMIT. KEEP WA RM/QUIET CALL MD. BEWARE OF ASPIRATION INTO LUNGS.

#### Fire Fighting

Flash Point Method:CC Flash Point:55.0F,12.8C

Lower Limits:1%

Extinguishing Media: CARBON DIOXIDE OR DRY CHEMICALS FOR SMALL FIRES.

FOAM FOR LARGE FIRES.

Fire Fighting Procedures: COOL CLSD CNTNRS W/WATER SPRAY. WEAR



NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard: CAUTION-CLSD CNTNRS MAY BUILD EXPLO PRESS FROM HEAT. VAPS ARE HVR/AIR & MAY TRAVEL ALONG GROUND OR MAY BE MOVED BY VENT & IGNITED BY PILOT LIGHTS, (SUPP DATA)

#### **Accidental Release**

Spill Release Procedures: SHUT OFF LEAK. ELIMINATE IGNITION SOURCES. WEAR PROT EQUIP. DIKE W/INERT MATL & TRANSFER W/NON-SPARKING TOOLS THE LIQ & SOLID TO SEPARATE CNTNRS. REMOVE CONTAMINATED CLTHNG & WASH SKIN. KEEP SPILL OUT OF MUNICIPAL SEWERS & OPEN BODIES OF WATER.

#### Handling

Handling and Storage Precautions: KEEP DRUM OUT OF SUN/AWAY FROM HEAT. GROUND AS EMPTYING-LIMIT FREE FALL TO A FEW INCHES. NEVER USE PRESS TO EMPTY DRUM. KEEP CLSD TIGHT WHEN NOT USING Other Precautions: FOR INDUSTRIAL USE ONLY. USE ONLY W/ADEQUATE VENT. AVOID BUILD/BRTHNG OF VAP. DO NOT INGEST. AVOID CNTCT W/EYES/SKIN.EMPTY CNTR MAY BE HAZARD-MAY CONTAIN EXPLOS VAP/DANGEROUS RESIDUE.

## **Exposure Controls**

Respiratory Protection: NIOSH/MSHA APPROVD FOR SPECIFIC EXPOSURE OF CONCERN.

Ventilation: ADEQUATE TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves: RESISTANT TYPE Eye Protection: CHEM SPLASH GOGGLES

Other Protective Equipment: NORMAL CLTHNG COVERING ARMS/LEGS. EYE/SAFETY

SHOWER.

Supplemental Safety and Health

CONTAINER SIZE:1 GAL. EMERGENCY PHONE #:215-459-5320(NIGHT). HAZ INGRED:SE7555000 VM & P NAPHTHA, 24.5%,TLV 300 PPM/ZE2100000 XYLENE,

#### **Chemical Properties**

HCC:F2 Vapor Pres:SEE INGS Vapor Density:HVR/AIR Spec Gravity:1.318

Appearance and Odor: RED PAINT

## **Stability**

Stability Indicator/Materials to Avoid:YES AVOID CONTACT WITH STRONG OXIDIZING AGENTS. Stability Condition to Avoid:EXCESSIVE HEAT, SPARKS, AND OPEN FLAME. Hazardous Decomposition Products:CO,CO\*2, VARIOUS HYDROCARBONS, ACROLEIM,ETC.

## **Disposal**

Waste Disposal Methods:INCINERATE LIQUID IN APPROVED EQUIP. LANDFILL CONTAMINATED DIKING MATL(DRY SAND, FULLER'S EARTH, ETC)IN A POSTED TOXIC SUBSTANCE LANDFILL IN ACCORDANCE W/LOCAL,STATE & FEDERAL REGULATIONS. SUBJ TO SPO NTANEOUS COMB:STORE IN FIRE PROOF CNTNRTIL RMVD

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.