

L#1378,RED DECK,MIL-E-18210A

MSDS Number

BDVQP

National Stock Number

8010-00-292-1812

Product Name

L#1378,RED DECK,MIL-E-18210A

Manufacturer

PRESERVATIVE PAINT COMPANY

Product Identification

Product ID:L#1378,RED DECK,MIL-E-18210A

MSDS Date:01/01/1985

FSC:8010

NIIN:00-292-1812

MSDS Number: BDVQP

Responsible Party

PRESERVATIVE PAINT COMPANY

5410 AIRPORT WAY S

SEATTLE , WA 98108-1726

US

Cage: 86589

Contractor

PRESERVATIVE PAINT CO

80387

SEATTLE, WA 98108-1726

US

Cage: 86589

Ingredients

PIGMENTS(TYPE NOT SPECIFIED)

Fraction By Weight: 36%

STANDARD OIL 350B(CONTAINS 31% PARAFFINS

Fraction By Weight: 32%

DRIER (TYPE NOT SPECIFIED)

Fraction By Weight: 1%

ALKYD RESIN(CONFORMS TO SPECIFICATION TT-R-266-I)

Fraction By Weight: 15%

VARNISH(CONFORMS TO SPECIFICATION MIL-V-15218-II)

Fraction By Weight: 16%

Hazards

Effects of Overexposure: INHAL OF HIGH VAPOR CONCS OR MISTS MAY LEAD TO ASPHYXIATION. PROMPT REMOVAL TO FRESH AIR IS IMPORTANT

First Aid

First Aid: SKIN: WASH THOROUGHLY W/ SOAP & WATER. REMOVE CONTAMINATED CLOTHING & WASH BEFORE REUSE. EYES: IMMEDIATELY FLUSH W/ WATER AT LEAST 15 MINS. CALL MD. INGESTION: DO NOT INDUCE VOMITING CALL MD. INHALATION: REMOVE TO FRESH AIR IMMEDIATELY.

Fire Fighting

Flash Point: 104F TCC
Lower Limits: 0.8
Upper Limits: 6.8
Extinguishing Media: CO₂, DRY CHEMICAL
Fire Fighting Procedures: ELIMINATE ALL SOURCES OF IGNITION

Accidental Release

Spill Release Procedures: EXTINGUISH ALL SURCES OF IGNITION IN VICINITY OF SPILL OR RELEASED VAPORS. CLEAN UP SPILLS AS SOON AS POSSIBLE. ABSORB LARGE SPILLS W/ CLAY OR DIATOMACEOUS EARTH

Handling

Handling and Storage Precautions: STORE IN COOL, WELL-VENTILATED AREA AWAY FROM SOURCES OF IGNITION. CONTAINERS SHOULD HAVE A COMBUSTBLE LIQUID "CAUTION" LABEL.

Exposure Controls

Respiratory Protection: ORGANIC VAPOR RESP; SELF-CONTAINED APRTS IF VAPOR CONC > TLV
Ventilation: LOCAL EXHAUST IF VAPOR CONCENTRATIONS EXCESSIVE
Protective Gloves: NEOPRENE/ RUBBER
Eye Protection: CHEM. SFTY GOGGLES IF SPL
Supplemental Safety and Health
VAPOR PRESSURE: 0.3 MMHG. MFG SUGGESTS TLV OF 250 PPM

Chemical Properties

HCC: F4
Boiling Pt: B.P. Text: 311 TO 386F
Vapor Density: 4.8
Spec Gravity: 1.265
Evaporation Rate & Reference: 0.12 BUTYL ACETATE
Solubility in Water: NEGLIGIBLE
Percent Volatiles by Volume: 53.3

Stability

Stability Indicator/ Materials to Avoid: YES
MAY REACT WITH STRONG OXIDIZING MATERIALS
Hazardous Decomposition Products: NRML CMSTN-CO₂, WATER
VAPOR; INCOMP. CMBSTN-CO

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE W/ LOCAL, STATE & FEDERAL CODES

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.