https://msdsreport.com/msds/BDVYB

741612 GRAY 36231

MSDS Number

BDVYB

National Stock Number

8010-00-297-0550

Product Name

741612 GRAY 36231

Manufacturer

PRATT AND LAMBERT

Product Identification

Product ID:741612 GRAY 36231 MSDS Date:01/01/1985 FSC:8010 NIIN:00-297-0550 MSDS Number: BDVYB

Responsible Party

PRATT AND LAMBERT

Emergency Phone: 316-733-1361

Cage: 61196

Contractor

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

MINERAL SPIRITS CAS: 64475-85-0 RTECS: PY8240000 Fraction By Weight: 35%

ACGIH TLV: 500 PPM

METHYL ALCOHOL (METHANOL) (SARA III) CAS: 67-56-1 RTECS: PC1400000 Fraction By Weight: OSHA PELS,200PPM/250STEL ACGIH TLV: S,200PPM/250STEL; 93 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

Hazards

TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION

First Aid

First Aid:CONTACT-FLUSH SKIN AND EYES WITH WATER WHILE REMOVING CONTAMINATED CLOTHING. INHALATION-REMOVE TO FRESH AIR. CALL PHYSICIAN IF SYMPTOMS PERSIST.

•

Fire Fighting

Flash Point:104F, 40C TCC Lower Limits:1.10 Extinguishing Media:NFPA CLASS B EXTINGUISHER; POLYMER FOAM FOR LARGE FIRES Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120F STORE LARGE QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106 Other Precautions: GROUND CONTAINERS WHEN POURING. AVOID FREE FALL OF LIQUID IN XS OF FEW INCHES DO NOT FLAME CUT, BRAZE OR WELD COATED MATERIAL WITHOUT BUR OF MINES APPROVED RESPIRATOR OR APPROPRIATE VENTILATION

Exposure Controls

Respiratory Protection:OPEN AREA:BUR MINES MECH RESPIRATOR;CLOSED:BUR MINES CHEM/MECH FILTE Ventilation:GENERAL DILUTION OR LOCAL EXHAUST TO KEEP TLV BELOW LIMIT Protective Gloves:REQ IF LONG CON Eye Protection:TO PROTECT VS SPLASHING Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING. Supplemental Safety and Health

Chemical Properties

HCC:F4 Boiling Pt:B.P. Text:311-373F Vapor Density:>AIR Evaporation Rate & Reference:SLOWER THAN ETHER Percent Volatiles by Volume:58

Stability

Stability Indicator/Materials to Avoid:YES

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS-INCINERATE IN APPROVED FACILITY-DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.