

744702 EN ALKYD LUST QD BLACK 37038

MSDS Number

BDWCJ

National Stock Number

8010-00-297-0800

Product Name

744702 EN ALKYD LUST QD BLACK 37038

Manufacturer

PRATT AND LAMBERT

Product Identification

Product ID:744702 EN ALKYD LUST QD BLACK 37038

MSDS Date:01/01/1985

FSC:8010

NIIN:00-297-0800

MSDS Number: BDWCJ

Responsible Party

PRATT AND LAMBERT

16116 E 13TH ST

WICHITA , KS 67201

US

Cage: 61196

Contractor

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

ALIPHATIC NAPHTHA

Fraction By Weight: 15%

ACGIH TLV: 200 PPM

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

Fraction By Weight: 7.5%

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

VM&P NAPHTHA

RTECS: ZB1600000

Fraction By Weight: 15%

ACGIH TLV: 200 PPM

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight:

ACGIH TLV: 500 PPM

Hazards

Effects of Overexposure: INHALATION-ANESTHETIC, IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

First Aid

First Aid: CONTACT-FLUSH SKIN AND EYES WITH WATER WHILE REMOVING CONTAMINATED CLOTHING. INHALATION-REMOVE TO FRESH AIR. CALL PHYSICIAN IF SYMPTOMS PERSIST.

Fire Fighting

Flash Point: 13F, -10C

Extinguishing Media: NFPA CLASS B EXTINGUISHER; POLYMER FOAM FOR LARGE FIRES

Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE

Unusual Fire/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120F STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106
Other Precautions: GROUND CONTAINERS WHEN POURING. AVOID FREE FALL OF LIQUID IN XS OF FEW INCHES DO NOT FLAME CUT, BRAZE OR WELD COATER MATERIAL WITHOUT BUR OF MINES APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

Exposure Controls

Respiratory Protection: OPEN AREA: BUR MINES MECH RESPIRATOR; CLOSED: BUR MINES CHEM/MECH FILTE

Ventilation: GENERAL DILUTION OF LOCAL EXHAUST TO KEEP TLV BELOW LIMIT

Protective Gloves: REQ IF LONG CON

Eye Protection: TO PROTECT VS SPLASHING

Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT TO

CONTAMINATED CLOTHING
Supplemental Safety and Health

Chemical Properties

HCC:F3
Boiling Pt:B.P. Text:193-290F
Vapor Density:Evaporation Rate & Reference:SLOW/ETHER
Percent Volatiles by Volume:63

Stability

Stability Indicator/Materials to Avoid:YES

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS-INCINERATE IN APPROVED FACILITY-DO NOT
INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.