

## **MD-8958,F-155,MIL-P-24441**

### **MSDS Number**

BDYDY

### **National Stock Number**

8010-00-410-8469

### **Product Name**

MD-8958,F-155,MIL-P-24441

### **Manufacturer**

DEVOE AND RAYNOLDS CO INC

### **Product Identification**

Product ID:MD-8958,F-155,MIL-P-24441

MSDS Date:01/01/1985

FSC:8010

NIIN:00-410-8469

Kit Part:Y

MSDS Number: BDYDY

### **Responsible Party**

DEVOE & RAYNOLDS CO., INC.

4000 DUPONT CIR

LOUISVILLE , KY 40207

US

Cage: EO559

### **Contractor**

DEVOE AND RAYNOLDS CO DIV OF GROW GROUP INC

7600

LOUISVILLE, KY 40207

US

502-361-2536/502-589-9340

Cage: 6R552

### **Ingredients**

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight: 15.0%

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: DE3030000

Fraction By Weight: 10.0%

OSHA PEL100 PPM

## Hazards

Effects of Overexposure:ACUTE:(INH)HEADACHE, NAUSEA, DIZ;(SKIN)PRLNG/REPEATED CNTCT CAUSES IRRIT. CHRONIC:IRRIT

## First Aid

First Aid:IH:MOVE TO FRESH AIR. SKIN:FLUS W/LG AMT OF WATER.REMOVE CONTAMINATED CLOTHING. EYE:IMMED FLUSH W/CLEAN WATER AT LEAST 15 MIN. CALL MD.

## Fire Fighting

Flash Point:>99F PMCC  
Lower Limits:1.0  
Extinguishing Media:CO\*2, DRY CHEMICAL, FOAM  
Unusual Fire/Explosion Hazard:WATER SHOULD BE USED TO COOL CONTAINERS EXPOSED TO FIRE

## Accidental Release

Spill Release Procedures:AVOID BREATHING VAPORS.EXTINGUISH IGNITION SOURCES IN IMMEDIATE AREA.AVOID CONTACT W/LIQUID.SOAK UP SPILLS ON SAWDUST OR OTHER ABSORBENT SOLID & STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED

## Handling

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPERATURE OR NEAR FIRE OR OPEN FLAME  
Other Precautions:CLOSE CONTAINERS AFTER USE. DO NOT REUSE EMPTY CONTAINERS.

## Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED AIR-SUPPLY MASK IN UNVENTILATED/CONFINED AREAS.  
Ventilation:SUFFICIENT TO KEEP TLV/LEL BELOW LIMIT. USE EXPL-PROOF EQUI  
Protective Gloves:SOLV RESISTANT  
Eye Protection:REQ D SOLV RESISTANT  
Other Protective Equipment:NORMAL PROTECTIVE CLOTHING  
Supplemental Safety and Health  
VAPOR DENSITY:HEAVIER THAN AIR. WT PER GALLON: 10.3 LBS.  
DOT:COMBUSTIBLE LIQUID.KEY1:F4.

## Chemical Properties

HCC:F4  
Boiling Pt:B.P. Text:211-355F  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:39.

## Stability

Stability Indicator/Materials to Avoid:YES  
OXIDIZING MATERIALS; RUBBER SOFTENS  
Hazardous Decomposition Products:CO, CO\*2, AMINE COMPOUNDS

## Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FED, STATE & LOCAL CODES

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.