

ISOPAR G.(133464-00644)

MSDS Number

BFBACK

National Stock Number

6810-00-484-3430

Product Name

ISOPAR G.(133464-00644)

Manufacturer

EXXON COMPANY U S A

Product Identification

Product ID:ISOPAR G.(133464-00644)

MSDS Date:01/01/1987

FSC:6810

NIIN:00-484-3430

MSDS Number: BFBCK

Responsible Party

EXXON COMPANY,U.S.A.

1251 AVE OF THE AMERICAS

NEW YORK , NY 10020-1104

US

Emergency Phone: 800-424-9300

Cage: EO384

Contractor

EXXON COMPANY,USA

2180

NEW YORK, NY 10020-1104

US

713-870-6000

Cage: 2F871

Ingredients

HYDROTREATED HEAVY NAPHTHA(PETROLEUM),(IT CONSISTS

Fraction By Weight: 100%

Hazards

Effects of Overexposure:HIGH VAPOR CONC IRRITATES EYES,RESPIRATORY TRACT;HEADACHES,DIZZINESS,ANESTHETIC,DERMATITIS.

First Aid

First Aid:SKIN:WASH W.SOAP & H*2O. EYES:FLUSH W. H*2O. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

Fire Fighting

Flash Point:100F/38C(TCC)

Autoignition Temp:Autoignition Temp Text:560F

Lower Limits:0.8

Upper Limits:7

Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.

Accidental Release

Spill Release Procedures:ELEMINATE IGNITION SOURCE.KEEP PEOPLE AWAY.RECOVER FREE PRODUCT.ADD SUITABLE ABSORBENT TO SPILL AREA.MINIMIZE BREATHING VAPOR OR SKIN CONTACT.VENTILATE AREA.KEEP PRODUCT OUT OF SEWER OR WATERCOURSE.OR EXPENSIVE LAND AREAS.

Handling

Handling and Storage Precautions:MINIMIZE BREATHING VAPORS & SKIN CONTACT.

Exposure Controls

Respiratory Protection:IF EXCED TLV,NIOSH/MSHA APPR SELF-CNTND BRTHG APP (POS PR MODE)
Ventilation:PROVIDE GREATER THAN 60 FEET PER MIN HOOD FACE VELOCITY.
Protective Gloves:CHEM-RESISTANT.
Eye Protection:CHEM SPLASH GOGGLES
Other Protective Equipment:IMPERVIOUS APRON.
Supplemental Safety and Health
MSDS DATED 11-14-86. "INCOMPAT.":& SODIUM OR CACIUM HYPOCHLORITE.

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:311-348F
Vapor Pres:10
Vapor Density:5
Spec Gravity:0.75
Viscosity:0.99 CP, 25C
Evaporation Rate & Reference:0.3, BUAC=1
Solubility in Water:Appearance and Odor:CLEAR WATER-WHITE LIQ,FAINT PETROL HYDROCAR. ODOR
Percent Volatiles by Volume:100

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS SUCH AS LIQUID CL*2 OR CONC O*2, "SEE SUPP"
Hazardous Decomposition Products:FUMES,SMOKE,CO,ALDEHYDES.

Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.