

1023

MSDS Number

BFBFR

National Stock Number

6820-00-487-9985

Product Name

1023

Manufacturer

E I DUPONT DEMEMOURS

Product Identification

Product ID:1023

MSDS Date:01/01/1985

FSC:6820

NIIN:00-487-9985

MSDS Number: BFBFR

Responsible Party

E.I.DUPONT DEMEMOURS

1007 MARKET STREET

WILMINGTON , DE 19899

US

Emergency Phone: 800-441-7515

Info Phone: 800-441-7515

Cage: LO450

Contractor

E.I.DUPONT DEMEMOURS

1635

WILMINGTON, DE 19899

US

800-441-7515

Cage: LO450

Ingredients

BENZENE (SARA III)

CAS: 71-43-2

RTECS: CY1400000

OSHA PEL1PPM/5STEL;1910.1028

ACGIH TLV: 10 PPM; A2; 9192

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of

Overexposure:DIZZINESS,SUFFOCATION,NAUSEA,HEADACHE,WEAKNESS,ANEMIA,
FATIGUE,RESPIRATORY IRRITATION,EDEMA,ANEMIA.

First Aid

First Aid:REMOVE TO FRESH AIR.IRRIGATE EYES WITH WATER.WASH
CONTAMINATED AREAS OF BODY WITH SOAP & WATER.STOMACH WASH,IF
SWALLOWED,FOLLOWED BY SALINE CATHARSIS.ARTIFICIAL RESPIRATION &
OXYGEN IF NECESSARY.NO ADR ENALIN SHOULD BE USED AS A RESPIRATORY
SIMULANT.

Fire Fighting

Flash Point:Extinguishing Media:SML FIRES:DRY CHEMICAL OR CO*2.LG FIRES:WATER SPRAY
OR FOG.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:MAY BE IGNITED BY
HEAT,SPARKS,FLAMES.CONTAINER MAY EXPLODE IN HEAT OF
FIRE.FLamm.VAPORS MAY SPREAD

Accidental Release

Spill Release Procedures:NO FLARES,SMOKING OR FLAMES IN HAZARD
AREA.STOP LEAK IF WITHOUT RISK.USE WATER SPRAY TO REDUCE VAPORS.LG
SPILLS:DIKE FOR LATER DISPOSAL.SMALL SPILLS:TAKE UP WITH SAND,EARTH
OR OTHER NONCOMBUSTIBLE ABSORBENT MATERIAL

Handling

Handling and Storage Precautions:PROTECT AGAINST PHYSICAL
DAMAGE.OUTDOOR OR DETACHED STORAGE IS PREFERABLE.INDOOR STORAGE
SHOULD BE IN A STD FLAMMABLE LIQUID STORAGE ROOM.

Other Precautions:SPARK RESISTANT TOOLS SHOULD BE USED.WEAR CHEMICAL
SAFETY GOGGLES,FACE SHIELD SELF-CONTAINED BREATHING APPARATUS &
RUBBER PROTECTIVE CLOTHING.

Exposure Controls

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS

Ventilation:AS REQUIRED TO CONTROL TLV IN AIR

Protective Gloves:RUBBER

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:RUBBER PROTECTIVE CLOTHING,FACE SHIELD

Supplemental Safety and Health

MFG MAY USE EITHER BENZENE,TOLUENE OR XYLENE

Chemical Properties

HCC:F2

Solubility in Water:SLIGHT

Appearance and Odor:COLORLESS LIQUID,AROMATIC ODOR

Stability

Stability Indicator/Materials to Avoid: YES
OXIDIZING MATERIALS & IGNITION SOURCES

Disposal

Waste Disposal Methods: SPRAY INTO A FURNACE UNDER CONTROLLED CONDITIONS FOR INCINERATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.