

## **WAX-SEAL**

### **MSDS Number**

BFBGH

### **National Stock Number**

7930-00-489-5606

### **Product Name**

WAX-SEAL

### **Manufacturer**

KARSCAL CORP

### **Product Identification**

Product ID:WAX-SEAL  
MSDS Date:01/01/1985  
FSC:7930  
NIIN:00-489-5606  
MSDS Number: BFBGH

### **Responsible Party**

KARSCAL CORPORATION  
Emergency Phone: 213-877-0168  
Cage: LO454

### **Contractor**

KARSEAL CORP  
NORTH HOLLYWOOD, CA 91605-6228  
US  
818-765-9852  
Cage: 05164

### **Ingredients**

KEROSENE  
CAS: 8008-20-6  
RTECS: OA5500000  
Fraction By Weight: 16.8%  
ACGIH TLV: 275

ALIPHATIC NAPHTHA  
Fraction By Weight: 54.9%  
ACGIH TLV: 25

### **Hazards**

Effects of Overexposure:ACUTE:INHALE-ANETH.IRRITATES RESP TRACT.HARMFUL  
OR FATAL IF SWALLOWED

### **First Aid**

First Aid:SKIN CONTACT-FLUSH WITH WATER. FOR EYES-FLUSH WATER-15 MINS  
AND GET MED.ATTN. AFTER HIGH EXPO-GET AIR,RESTORE BREATHING. IF  
SWALLOWED,CALL DOCTOR IMMEDIATELY. DO NOT INDUCE VOMITTING.

### **Fire Fighting**

Flash Point:63C

Lower Limits:1.3  
Upper Limits:NA  
Extinguishing Media:CO2,DRY CHEMICAL FOAM  
Fire Fighting Procedures:WATER SPRAY INEFFECTIVE,BUT CAN PROTECT  
FIREFIGHTERS & COOL  
Unusual Fire/Explosion Hazard:COMBUSTIBLE! KEEP CONTAINER TIGHTLY  
CLOSED. ISOLATE FROM OXIDIZERS,HEAT AND OPEN FLAME.

## Accidental Release

Spill Release Procedures:ISOLATE FROM OXIDIZERS,HEAT AND OPEN FLAME.

## Handling

Handling and Storage Precautions:STORE IN A COOL AREA.KEEP AWAY FROM  
HEAT,SPARKS AND OPEN FLAME.EMPTY CONTAINERS HAZARDOUS! CONTINUE ALL  
LABEL PRECAUTIONS.

## Exposure Controls

Respiratory Protection:TLV USE SELF-CONT.AIR PACK.VENT TO KEEP SOLVCONC  
IN AIR BELOW 25PPM  
Ventilation:LOC EX-PREF. MECH EX-ACCEPTABLE SOLVENTS  
Protective Gloves:RECOMMENDED  
Eye Protection:REQUIRED  
Other Protective Equipment:NONE  
Supplemental Safety and Health  
SECTION IV-CLOSED CONTAINERS. USE FOG NOZZLES IF WATER IS USED. USE AIR  
SUPPLIED BREATHING MASKS,PROT CLOTH.

## Chemical Properties

HCC:N1  
Boiling Pt:B.P. Text:380-390F  
Vapor Pres:NA  
Vapor Density:NA  
Spec Gravity:1.79  
Evaporation Rate & Reference:NONE  
Solubility in Water:NEG  
Appearance and Odor:HARD WAXY SOLID. HYDROCARBON ODOR  
Percent Volatiles by Volume:0.05

## Stability

Stability Indicator/Materials to Avoid:YES  
ISOLATE FROM STRONG OXIDIZERS SUCH AS PERMANGANATE  
Stability Condition to Avoid:ISOLATE FROM HEAT AND OPEN FLAME  
Hazardous Decomposition Products:CARB DIOXIDE(FROM BURNING),CARBON  
MONOXIDE

## Disposal

Waste Disposal Methods:BURY IN LANDFILL AWAY FROM RIVERS AND STREAMS.  
OBSERVE LOCAL,STATE,FEDERAL HEALTH,SAFETY AND POLLUTION LAWS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.