

SODIUM METABISULFITE

MSDS Number

BFBLL

National Stock Number

6810-00-496-9555

Product Name

SODIUM METABISULFITE

Manufacturer

ALLIED CHEMICAL CORP

Product Identification

Product ID:SODIUM METABISULFITE MSDS Date:01/01/1987 FSC:6810 NIIN:00-496-9555 MSDS Number: BFBLL

Pesnonsihle Party

Responsible Party

ALLIED CHEMICAL CORP.

COLUMBIA RD & PARK AVE

MORRISTOWN, NJ 07960

US

Emergency Phone: NONE PROVIDED

Cage: 1L168

Contractor

ALLIED-SIGNAL INC

1087R

MORRISTOWN, NJ 07962-2332

US

201-455-4414 Cage: 1L164

Ingredients

SODIUM BISULFITE (SASA III)

CAS: 7631-90-5 RTECS: VZ2000000

Fraction By Weight: >97%

OSHA PEL5 MG/M3

ACGIH TLV: 5 MG/M3; 9192 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure:SHARP PUNGENT ODOR IRRITATES EYES & MUCOUS MEMBRANES;SKIN IRRITATION; INHALED/INGESTED DUST HARMFUL

First Aid

First Aid:REMOVE TO FRESH AIR;FLUSH EXPOSED AREA WITH H*20;FOR EYES,FLUSH WITH H*20 FOR 15 MIN,GET IMMEDIATE MEDICAL



ATTN;INGESTED:INDUCE VOMITING.CALL PHYSICIAN AT ONCE:INHALATION:DUST OR FUMES,GET MEDICAL ATT ENTION AT ONCE.

Fire Fighting

Extinguishing Media: N/A; NON FLAMMABLE

Fire Fighting Procedures: FULL FACE, SELF-CNTND BRTHG APP, NIOSH APPR FOR SO*2 GAS

Unusual Fire/Explosion Hazard:HEAT RELEASES SO*2 GAS;CONTACT W WATER RELEASES SO*2 GAS AND GIVES MILDLY ACIDIC SOLUTION

Accidental Release

Spill Release Procedures: DO NOT TOUCH SPILLED MATERIAL; SM SPILL: CAREFULLY SWEEP UP & REMOVE; LG SPILL: CAREFULLY SHOVEL UP & REMOVE; NEUTRALIZE RESIDUE WITH ALKALI & FLUSH WITH WATER; AVOID DUSTING CONDITIONS.

Handling

Handling and Storage Precautions:STORE UNDER COVER IN COOL,DRY,WELL VENTILATED AREA;DO NOT STORE NEAR ACIDS OR OXIDIZING AGENTS. Other Precautions:AVOID BREATHING DUST OR ANY RELEASED SULFUR DIOXIDE FUMES. USE NIOSH/MESA APPROVED SULFUR DIOXIDE RESPIRATOR OR SELF-CONTAINED BREATHING APPARATUS.

Exposure Controls

Respiratory Protection: NIOSH/MESA APPR DUST OR SO*2 GAS

RESPIRATOR; SELF-CNTND BRTHG APP

Ventilation: PROVIDE ADEQUATE EXHAUST TO MAINTAIN UNDER EXPOSURE, LOW

DUST

Protective Gloves:RUBBER;PLASTIC Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment: NORMAL WORK CLOTHNG TO PROTECT SKIN FROM

DUST; EYE WASH FOUNT

Supplemental Safety and Health

MSDS DTD 6/82.

Chemical Properties

HCC:C1

Boiling Pt:B.P. Text:DECOMP 150C

Spec Gravity: 1.48

Solubility in Water: APPRECIABLE

Appearance and Odor: FINE WHITE GRANULAR POWDER; ODOR OF SULFER DIOXIDE

Stability

Stability Indicator/Materials to Avoid:YES

ALL OXIDIZING AGENTS; ACIDS;

Stability Condition to Avoid:PROTECT FROM ABOVE-AMBIENT HEAT & MOISTURE Hazardous Decomposition Products:SULFUR DIOXIDE GAS

Disposal

Waste Disposal Methods: NEUTRALIZE TO PH 9 IN EXCESS OF WATER, THEN OXIDIZE TO SULFATE BY BLOWING WITH AIR OR TREATING WITH WEAK HYDROGEN PEROXIDE. TREATED WASTE MAY BE FLUSHED DOWN SEWER WITH EXCESS WATER, IF LOCAL REGULATION S PERMIT.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.