

BRAYCOTE 103

MSDS Number

BFBLS

National Stock Number

8030-00-497-2513

Product Name

BRAYCOTE 103

Manufacturer

BRAY OIL COMPANY INC

Product Identification

Product ID:BRAYCOTE 103 MSDS Date:01/01/1985 FSC:8030 NIIN:00-497-2513

NIIN:00-497-2513 MSDS Number: BFBLS

Responsible Party

BRAY OIL COMPANY, INC

16715 VON KARMAN AVE., SUITE230

IRVINE, CA 92714

US

Emergency Phone: 714-660-9414

Info Phone: 714-660-9414

Cage: EO565

Contractor

CASTROL INDUSTRIAL NORTH AMERICA INC SPECIALTY PRODUCTS

DOWNERS GROVE, IL 60515-1280

US

630-241-4140 Cage: 2R128

Ingredients

ALIPHATIC HYDROCARBON

Fraction By Weight: 37.0% ACGIH TLV: 500 PPM (MFG)

Hazards

Effects of Overexposure: DROWSINESS, HEADACHE, NAUSEA, NARCOSIS

First Aid

First Aid:INHALATION:REMOVE TO FRESH AIR. SKIN:SOAP&WATER WASH.EYES:FLUSH WITH WATER CONTACT MD.INGESTION:DO NOT INDUCE VOMITING, CONTACT PHYSSCIAN IMMEDIATELY.

Fire Fighting

Flash Point:100F PMCC Lower Limits:1.0 Upper Limits:6.0

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG Fire Fighting Procedures:USE WATER ONLY TO COOL FIRE EXPOSED CONTAINERS



Unusual Fire/Explosion Hazard: FLAMMABLE LIQUID & MODERATE FIRE HAZARD. POSSIBLE EXPLOSION HAZARD.

Accidental Release

Spill Release Procedures: AVOID ALL IGNITION SOURCES. VENTILATE ROOM. WIPE UP WITH RAGS, USE GLOVES, OR USE SLOP OIL DISPOSAL AGENT. STORE IN COVERED META CONTAINER & DISPOSE OF AS SOON AS POSSIBLE.

Handling

Handling and Storage Precautions: NORMAL PRECAUTIONS IN HANDLING PETROLEUM PRODUCTS. STORE IN WELL VENTILATED AREA AWAY FROM SOURCES OF HEAT & IGNITION.

Other Precautions: KEEP IN CLOSED META CONTAINERS.

Exposure Controls

Respiratory Protection: USE AIR-MASK IF IN ENCLOSED AREA.

Ventilation: MECHANICAL EXHAUST RECOMMENDED

Protective Gloves:BUNA N Eye Protection:SPLAS GOGGLES

Other Protective Equipment: AS NEEDED TO PREVENT SKIN CONTACT

Supplemental Safety and Health

VAP-DENS: >1. BRAYCOTE 103 MEETS GRADE 1,MIL-C-16173 SPECIFICATIONS.

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:310F Spec Gravity:0.912

Evaporation Rate & Reference: Solubility in Water: NEGLIGIBLE

Appearance and Odor: BLACK LIQUID ASPHALT; PETROLEUM SOLVENT ODOR

Percent Volatiles by Volume: 37.0

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Hazardous Decomposition Products:CO,CO*2,SO*2& SMOKE

Disposal

Waste Disposal Methods: INCINERATE IN ACCORDANCE WITH ALL LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.