

92-2285 DISPERSANT (KIT CATALOG #92-2085)

MSDS Number

BFBMQ

National Stock Number

6850-00-498-2345

Product Name

92-2285 DISPERSANT (KIT CATALOG #92-2085)

Manufacturer

A B DICK CO

Product Identification

Product ID:92-2285 DISPERSANT (KIT CATALOG #92-2085)

MSDS Date:01/01/1987

FSC:6850

NIIN:00-498-2345

Kit Part:Y

MSDS Number: BFBMQ

Responsible Party

A.B.DICK CO.

5700 WEST TOUHY AVENUE

CHICAGO , IL 60648-4606

US

Emergency Phone: 312-647-8800

Info Phone: 312-547-8800

Cage: HO951

Contractor

DICK A B CO

CHICAGO, IL 60648

US

312-647-8800

Cage: HO951

Ingredients

PETROLEUM DISTILLATE (ALIPHATIC),CAS #68551-16-6

Fraction By Weight: 100%

ACGIH TLV: 300PPM(MFR)

Hazards

Effects of Overexposure:DROWSINESS, EYE & SKIN IRRITATION.

First Aid

First Aid:INHALE: RMV TO FRESH AIR. IF NOT BRTHG GIVE CPR. IF BRTHG DIFFICULT GIVE OXYGEN. INGEST: DO NOT INDUCE VOMITING. CONTACT: IMMED FLUSH EYES OR SKIN W/ PLENTY OF WATER. CALL A PHYSICIAN.

Fire Fighting

Flash Point:104F,40C,TCC

Lower Limits:0.8

Upper Limits:7.0

Extinguishing Media:CARBON DIOXIDE, FOAM

Fire Fighting Procedures:WEAR CHEM PROT. SUIT WITH SCBA. COOL CONTRS WITH H*2O.

Unusual Fire/Explosion Hazard:FLASHBACK ALONG VAPOR TRAIL MAY OCCUR; VAP MAY EXPL. IF IGNITED IN AN ENCLOSED AREA.

Accidental Release

Spill Release Procedures:WIPE UP W/CLOTH OR ABSORBENT. FLUSH RESIDUE W/WATER.

Handling

Handling and Storage Precautions:STORE IN COOL, DRY AREA, AWAY FROM HEAT, FIRE, IGNITION SOURCES. PROCEDURES FOR HANDLING/STORAGE SAME AS FOR HYDROCARBONS OR LIGHT OILS WITH FP-105F TCC.

Exposure Controls

Respiratory Protection:NONE SPECIFIED

Ventilation:LOCAL EXHAUST TO MAINTAIN MODERATE VENTILATION.

Protective Gloves:RUBBER/PLASTIC

Eye Protection:AS REQUIRED

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Supplemental Safety and Health

MSDS DATED 05-28-85/SEE P/N IND A AND/OR C FOR TONER/CATALOG #92-2085 IS FOR THE KIT CONTAINING BOTH DISPERSANT & TONER.

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:>315F/177C

Vapor Pres:Vapor Density:5.0

Spec Gravity:0.748

Evaporation Rate & Reference:NOT AVAILABLE

Solubility in Water:INSOLUBLE

Appearance and Odor:LIQUID;NO COLOR;GASOLINE ODOR

Percent Volatiles by Volume:100

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HEAT, IGNITION SOURCES

Hazardous Decomposition Products:NONE NOTED,BUT EXPECT CO, CO*2, H*2O.

Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.