

17875 WHITE

MSDS Number

BFCBN

National Stock Number

8010-00-515-1596

Product Name

17875 WHITE

Manufacturer

PRAXAIR INC

Product Identification

Product ID:17875 WHITE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-515-1596

MSDS Number: BFCBN

Responsible Party

PRAXAIR INC

39 OLD RIDGEBURY RD

DANBURY , CT 06817-0001

US

Emergency Phone: 203-794-5782

Info Phone: 203-794-5782

Cage: 0LV01

Contractor

PRAXAIR, INC.

DANBURY, CT 06810-5113

US

800-772-9247; 800-PRAXAIR

Cage: 0LV01

Ingredients

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 45.0%

ACGIH TLV: 500 PPM

METHYL ETHYL KETOXIME

RTECS: PM7783000

Fraction By Weight:

Hazards

Effects of Overexposure:IRRIT OF NOSE,THROAT,EYES & POSS DIZZINESS & NAUSEA.SPRAY MISTCONTN LEAD.

First Aid

First Aid:INHAL: REMOVE FR EXPOSUR & PROVID FRESH AIR.SPLASH EYES-FLUSH IMMED W/LG AMTS OF WATER FOR 15 MIN.SPLASH SKIN:REMOV CONTAM CLOTHING & WASH ALL AFFECT AREA W/WATR.INGEST:DO NOT INDUC VOMITNG.CONSULT A D R. IMMED IN ALL CASES.

Fire Fighting

Flash Point:104 F 40 C TCC
Extinguishing Media:CLASS B EXTING, CARBON DIOXIDE, DRY CHEM OR ALCOHOL FOAM
Fire Fighting Procedures:SELF CONTAINED BREATH APPARAT,WATER MAY BE INEFFECTIVE.
Unusual Fire/Explosion Hazard:KEEP CONTNRS TIGHTHLY CLOS.ISOLAT FR HEAT,ELECTR EQPMT,SPARKS & OPN FLAME.DO NOT APPLY TO VRYHOT SUR

Accidental Release

Spill Release Procedures:REMOV ALL SOURCES OF IGNIT (FLAMES,HOT SURFACES,ELECTRICAL, STATIC OR FRICTIONAL SPARKS).VENTILAT AREA & AVOID BREATHING VAPORS.REMOV W/ INERT ABSORB & NON-SPARKING TOOLS.STEPS MUST BE TAKN TO PREVNT CONTAM OF GROUND WATR OR STREAMS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOV 120 F.STORE LG QUANTITIES IN COMPLIA W/OSHA 1910.106.CONTNRS SHLD BE GROUNDED & BONDED TO THE RECEIVING CONTNR.
Other Precautions:DO NOT CUT OR WELD ON EMPTY CONTAINER. DO NOT USE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER.

Exposure Controls

Respiratory Protection:NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY WHN SPRAYING IN OUTDR
Ventilation:PROVID GEN DILUT/LOC EXHAUST VENT TO KP CONCENT BELO ACEP TL
Protective Gloves:SOLVENT,IMPERME
Eye Protection:SAFETY EYEWR
Other Protective Equipment:PROTECTV EQPMT TO PRVNT SKN CONTCT.SE OSHA,29 CFR 1910.1025
Supplemental Safety and Health

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:311-373F
Vapor Density:>AIR
Evaporation Rate & Reference:Percent Volatiles by Volume:58

Stability

Stability Indicator/Materials to Avoid:YES
AVOID CONTCT W/STRONG ACIDS OR AKALINE MATERIALS.
Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES.
Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE & OXIDES OF CARBON & LEAD.
Conditions to Avoid Polymerization:DO NOT ADD DRIERS OR REACTIV CHEM W/O TECHN SUPERVISION.

Disposal

Waste Disposal Methods:DISPOSE IN ACCORD W/LOCAL, STATE & FEDERAL REGULATIONS.INCINERATIN EPA APPRVD FACILITY.DO NOT INCINERAT CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.