

WHITE 17875

MSDS Number

BFCDN

National Stock Number

8010-00-515-2256

Product Name

WHITE 17875

Manufacturer

AMERON INDUSTRIAL COATINGS DIV

Product Identification

Product ID: WHITE 17875

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00-515-2256

MSDS Number: BFCDN

Responsible Party

AMERON INDUSTRIAL COATINGS DIVISION

201 N BERRY ST

BREA , CA 92621-3904

US

Emergency Phone: 714-529-4597

Info Phone: 714-529-4597

Cage: 09869

Contractor

AMERON INDUSTRIAL COATINGS DIVISION

BREA, CA 92621-3904

US

714-529-4597

Cage: 09869

Ingredients

ETHYL ACETATE (SARA III)

CAS: 141-78-6

RTECS: AH5425000

Fraction By Weight: 31.6%

OSHA PEL400 PPM

ACGIH TLV: 400 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 27.6%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

N-BUTYL ACETATE (SARA III)

CAS: 123-86-4

RTECS: AF7350000

Fraction By Weight: 11.8%

OSHA PEL150 PPM/200 STEL

ACGIH TLV: 150 PPM/200STEL;9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

DIACETONE ALCOHOL (4-HYDROXY-4-METHYL-2-PENTANONE)

CAS: 123-42-2

RTECS: SA9100000

Fraction By Weight: 7.9%

OSHA PEL50 PPM

ACGIH TLV: 50 PPM; 9192

Hazards

Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

First Aid

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR.CALL A PHYSICIAN IF CONDITIONS PERSIST.

Fire Fighting

Flash Point:26F TCC

Lower Limits:1.6

Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE FIRES-FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES

Exposure Controls

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY
Supplemental Safety and Health
RESPIRATOR USE BASED ON CHEM. CONC. AND CONDITIONS OF USE.

Chemical Properties

HCC:F2
Boiling Pt:B.P. Text:158-342F
Vapor Density:>1
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:87.0

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID FIRE,HEAT AND HOT SURFACES

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND
FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.