

## **GACO N-700-A GREY**

### **MSDS Number**

BFCFK

### **National Stock Number**

8030-00-515-2488

### **Product Name**

GACO N-700-A GREY

### **Manufacturer**

GATES ENGINEERING CO INC

### **Product Identification**

Product ID:GACO N-700-A GREY

MSDS Date:01/01/1985

FSC:8030

NIIN:00-515-2488

MSDS Number: BFCFK

### **Responsible Party**

GATES ENGINEERING CO.,INC

100 S. WEST STREET

WILMINGTON , DE 19801

US

Emergency Phone: 302-656-9951

Info Phone: 302-656-9951

Cage: 88112

### **Contractor**

GATES ENGINEERING CO.,INC.

WILMINGTON, DE 19801

US

.....DISCONNECTED....

Cage: 88112

### **Ingredients**

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

PETROLEUM SOLVENTS

PIGMENTS

Fraction By Weight: 16%

VEHICLE (TYPE NOT SPECIFIED)

Fraction By Weight: 21%

## Hazards

Effects of Overexposure:SKIN/EYE CONT:BRIM IRRIT.INHALATION:IRRIT OF  
RESP TRACT,HEADACHE,DIZZINESS,UNCONSCIOUSNESS.

## First Aid

First Aid:INHAL:REMOVE TO FRESH AIR,RESTORE BREATH,NOTIFY MD.EYE:FLUSH  
W/WATER 15 MIN,TAKE TO DR.SKIN:WASH W/WATER,REMOVE CONTAMINATED  
CLOTHING,CONSULT DR.

## Fire Fighting

Flash Point:.40F/4C ASTM D

Lower Limits:0.9

Upper Limits:7

Extinguishing Media:DRY CHEMICAL,CARBON DIOXIDE,FOAM

Fire Fighting Procedures:SELF-CONT BREATH APPART,PROTECTIVE CLOTHING.

## Accidental Release

Spill Release Procedures:ABSORB AND DISPOSE OF IN ACCORDANCE WITH LOCAL  
REGS.REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA

## Handling

Handling and Storage Precautions:STORE IN COOL,DRY PLACE.USE ONLY WITH  
ADEQUATE VENTILATION.AVOID FLAMES,SPARKS,HOT SURFACES AND STRONG  
OXIDIZERS

Other Precautions:AVOID CONTACT WITH EYES AND SKIN.DO NOT TAKE  
INTERNALLY.EXHAUST SOLVENT VAPORS WHICH COLLECT NEAR FLOORS.

## Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH  
EXPOSURE OF CONCERN

Ventilation:LOCAL EXHAUST

Protective Gloves:RECOMMENDED

Eye Protection:RECOMMENDED

Supplemental Safety and Health

## Chemical Properties

HCC:F2

Vapor Density:>1

Spec Gravity:1

Evaporation Rate & Reference:Solubility in Water:NEGLIGIBLE

Appearance and Odor:GRAY,VISCOUS LIQUID COATING,CHARACTER SOLVENT ODOR

Percent Volatiles by Volume:76.1

## Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:SPRAKS,FLAMES,HOT SURFACES

Hazardous Decomposition Products:PROD OF COMBUST MAY INCLUDE CHLORINE

AND PHOSGENE

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGS.INCINERATE IN APPROVED FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.