

## **237H,NON-SKID DECK COAT RED (DISC W/O REPL)**

### **MSDS Number**

BFCFT

### **National Stock Number**

5610-00-515-9976

### **Product Name**

237H,NON-SKID DECK COAT RED (DISC W/O REPL)

### **Manufacturer**

DEVOE MARINE COATINGS CO

### **Product Identification**

Product ID:237H,NON-SKID DECK COAT RED (DISC W/O REPL)

MSDS Date:01/01/1985

FSC:5610

NIIN:00-515-9976

MSDS Number: BFCFT

### **Responsible Party**

DEVOE MARINE COATINGS CO.

4000 DUPONT CIRCLE

LOUISVILLE , KY 40207-4802

US

Cage: EO141

### **Contractor**

GROW GROUP INC DEVOE AND REYNOLDS CO DIV

LOUISVILLE, KY 40207-4802

US

502-361-2536

Cage: 97758

### **Ingredients**

NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: DE3030000

Fraction By Weight:

OSHA PEL100 PPM

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 10 - 20%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight:

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight:

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

2,4,6 - TRI(DIMETHYLAMINOMETHYL)PHENOL

CAS: 90-72-2

RTECS: SN3500000

Fraction By Weight:

## Hazards

Effects of Overexposure:SKIN/EYE: IRRITATION. INHALATION: IRRITATION OF RESPIRATORY TRACT,HEADACHE,NAUSEA,DIZZINESS

## First Aid

First Aid:EYE: FLUSH WITH WATER 15 MIN,CALL PHYSICIAN. SKIN: FLUSH WITH WATER,REMOVE CONTAMINATED CLOTHING. INHALATION: REMOVE TO FRESH AIR. INGESTION: CALL PHYSICIAN IMMEDIATELY.

## Fire Fighting

Flash Point:>80F/26C (SETA)

Extinguishing Media:CO\*2,DRY CHEMICAL,FOAM

Fire Fighting Procedures:SELF-CONT BREATH APP,WATER FOG TO COOL EXPOSED CONTAINERS

Unusual Fire/Explosion Hazard:DUE TO PRESSURE BUILD-UP,CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. CONTAIN SPILLED MATERIAL AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F/48C OR NEAR FIRE OR OPEN FLAME. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106.

Other Precautions:CLOSE CONTAINER AFTER USE. DO NOT REUSE EMPTY CONTAINERS.

## Exposure Controls

Respiratory Protection: NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN.  
Ventilation: GENERAL DILUTION/LOCAL EXHAUST WITH EXPLOSION PROOF MOTORS  
Protective Gloves: SOLVENT RESIST  
Eye Protection: SOLVENT RESIST EYEWEAR  
Other Protective Equipment: NORMAL PROTECTIVE CLOTHING.  
Supplemental Safety and Health  
TYPE 1. MFR ID CODE: FORMULA 237H, SPRAYABLE NON-SKID DECK COATING, MIL-D-24483A, TYPE 1. PKG: 5 GAL KIT.

## Chemical Properties

Boiling Pt: B.P. Text: 150F/65C  
Vapor Density: > 1  
Evaporation Rate & Reference: SLOWER THAN ETHER  
Percent Volatiles by Volume: 34

## Stability

Stability Indicator/Materials to Avoid: YES  
OXIDIZING MATERIALS, RUBBER SOFTENS  
Hazardous Decomposition Products: CO, CO\*2, OXIDES OF NITROGEN

## Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.