

EPOXO 2000XA,DULL BLACK,37038,PART B

MSDS Number

BFCGV

National Stock Number

5610-00-516-0050

Product Name

EPOXO 2000XA,DULL BLACK,37038,PART B

Manufacturer

AMERICAN ABRASIVE METALS CO

Product Identification

Product ID:EPOXO 2000XA,DULL BLACK,37038,PART B

MSDS Date:01/01/1987

FSC:5610

NIIN:00-516-0050

Kit Part:Y

MSDS Number: BFCGV

Responsible Party

AMERICAN ABRASIVE METALS CO

460 COIT ST

IRVINGTON , NJ 07111-4607

US

Cage: 88444

Contractor

AMERICAN SAFETY TECHNOLOGIES INC

ROSELAND, NJ 07068

US

973-403-2600

Cage: 88444

Ingredients

POLYAMIDE RESIN BLEND, CAS# N/R

TETRAETHYLENE PENTAMINE, CAS# 112-57-2

CAS: 112-57-2

RTECS: KH8585000

Fraction By Weight: 3-5%

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure:INHAL:DIZZ,UNCON.SKIN:IRRIT.EYE:IRRIT,DAMAGE.

First Aid

First Aid:EYE:FLUSH W/ LG AMT OF WATER.CALL MD.INHAL:FRESH AIR,O*2,ARTIF RESPIR.SKIN:WASH W/ SOAP & WATER.INGEST:DO NOT INDUCE VOMITING.CALL MD.

Fire Fighting

Flash Point:100F,38C PMCC
Lower Limits:1.4
Upper Limits:11.2
Extinguishing Media:CHEMICAL FOAM OR DRY CHEMICAL
Fire Fighting Procedures:USE SCBA W/ FULL FACE PIECE
Unusual Fire/Explosion Hazard:VAPORS MAY TRAVEL ALONG GROUND TO IGNITION SOURCES.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES(FLAMES,FLARES,PILOT LIGHTS,ELECTRICAL SPARKS).ABSORB ON SAND,CLAY OR OTHER ABSORBENT MATERIAL ANDSHOVEL INTO CONTAINERS.

Handling

Handling and Storage Precautions:DO NOT GET INTO EYES.AVOID CONTACT W/ SKIN & CLOTHING.AVOID INHAL OF VAP/MIST.USE W/ ADEQUATE VENT.WASH AFTER HANDLING.REMOVE,WASH CONTAM CLOTHING.
Other Precautions:AVOID EXTREME HEAT.DO NOT EXCEED 110F IN STORAGE AREA.KEEP AWAY FROM FLAME.

Exposure Controls

Ventilation:LOCAL EXHAUST,MECHANICAL VENT TO KEEP BELOW TLV
Protective Gloves:RUBBER,BUNAN
Eye Protection:CHEM SPLASH GOGGLES
Other Protective Equipment:PROTECTIVE CLOTHING
Supplemental Safety and Health
MSDS PREP:86302.PART B OF A 2-PART KIT. KEY1:F4.

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:243F,117C
Vapor Pres:5
Vapor Density:2.6
Spec Gravity:0.97
Evaporation Rate & Reference:0.7(BUAC=1)
Solubility in Water:MODERATE
Appearance and Odor:VISCOUS LIQUID,AMINE ODOR

Stability

Stability Indicator/Materials to Avoid:YES
STRONG ACID,OXIDIZING AGENTS
Hazardous Decomposition Products:CO,CO*2,TOXIC FUMES WHEN BURNING,NO*X

Disposal

Waste Disposal Methods:DISPOSE BY CONTROLLED BURNING OR AUTHORIZED LANDFILL IN ACCORDANCE W/ LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.