EPOXO 2000XA, WHITE, 27886, PART B

MSDS Number

BFCHC

National Stock Number

5610-00-516-0056

Product Name

EPOXO 2000XA, WHITE, 27886, PART B

Manufacturer

AMERICAN ABRASIVE METALS CO

Product Identification

Product ID:EPOXO 2000XA, WHITE, 27886, PART B MSDS Date:01/01/1987 FSC:5610 NIIN:00-516-0056

Kit Part:Y

MSDS Number: BFCHC **Responsible Party**

AMERICAN ABRASIVE METALS CO

460 COIT ST

IRVINGTON, NJ 07111-4607

US

Cage: 88444

Contractor

AMERICAN SAFETY TECHNOLOGIES INC

ROSELAND, NJ 07068

US

973-403-2600 Cage: 88444

Ingredients

POLYAMIDE RESIN BLEND CAS# N/R

TETRAETHYLENE PENTAMINE CAS# 112-57-2

CAS: 112-57-2

RTECS: KH8585000

Fraction By Weight: 3-5%

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: E01400000 OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS



Hazards

Effects of Overexposure:INHAL:DIZZ,UNCON.SKIN:IRRIT.EYE:IRRIT,DAMAGE.

First Aid

First Aid:EYE:FLUSH W/ LG AMT OF WATER.CALL MD.INHAL:FRESH AIR,O*2,ARTIF RESPIR.SKIN:WASH W/ SOAP & WATER.INGEST:DO NOT INDUCE VOMITING.CALL MD.

Fire Fighting

Flash Point: 100F, 38C PMCC

Lower Limits: 1.4 Upper Limits: 11.2

Extinguishing Media: CHEMICAL FOAM OR DRY CHEMICAL Fire Fighting Procedures: USE SCBA W/ FULL FACE PIECE

Unusual Fire/Explosion Hazard: VAPORS MAY TRAVEL ALONG GROUND TO

IGNITION SOURCES.

Accidental Release

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES (FLAMES, FLARES, PILOT LIGHTS, ELECTRICAL SPARKS). ABSORB ON SAND, CLAY OR OTHER ABSORBENT MATERIAL AND SHOVEL INTO CONTAINERS.

Handling

Handling and Storage Precautions: DO NOT GET INTO EYES.AVOID CONTACT W/ SKIN & CLOTHING.AVOID INHAL OF VAP/MIST.USE W/ ADEQUATE VENT.WASH AFTER HANDLING.REMOVE.WASH CONTAM CLOTHING.

Other Precautions: AVOID EXTREME HEAT. DO NOT EXCEED 110F IN STORAGE AREA. KEEP AWAY FROM FLAME.

Exposure Controls

Respiratory Protection: USE NIOSH/MSHA APPROVED SCBA IF EXCEED TLV Ventilation: LOCAL EXHAUST, MECHANICAL VENT TO KEEP BELOW TLV

Protective Gloves: RUBBER, BUNAN Eye Protection: CHEM SPLASH GOGGLES

Other Protective Equipment: PROTECTIVE CLOTHING

Supplemental Safety and Health

MSDS PREP: 86302. PART B OF A 2-PART KIT. ITEM IS TYPE 2 SPEC.

KEY1:F4.

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:243F,117C

Vapor Pres:5

Vapor Density: 2.6

Spec Gravity: 0.97

Evaporation Rate & Reference: 0.7 (BUAC=1)

Solubility in Water: MODERATE

Appearance and Odor: VISCOUS LIQUID, AMINE ODOR

Stability

Stability Indicator/Materials to Avoid:YES STRONG ACID,OXIDIZING AGENTS.

Hazardous Decomposition Products:CO,CO*2,TOXIC FUMES WHEN BURNING,NO*X

Disposal

Waste Disposal Methods: DISPOSE BY CONTROLLED BURNING OR AUTHORIZED LANDFILL IN ACCORDANCE W/ LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.





https://msdsreport.com/msds/BFCHC