

DEVTRAN

MSDS Number

BFCJM

National Stock Number

5610-00-519-1852

Product Name

DEVTRAN

Manufacturer

DEVOE AND RAYNOLDS CO INC

Product Identification

Product ID:DEVTRAN

MSDS Date:01/01/1985

FSC:5610

NIIN:00-519-1852

Kit Part:Y

MSDS Number: BFCJM

Responsible Party

DEVOE& RAYNOLDS CO, INC

2625 DURAHART ST

RIVERSIDE , CA 92507-2606

US

Emergency Phone: NONE

Cage: LO508

Contractor

DEVOE& RAYNOLDS CO, INC

RIVERSIDE, CA 92507-2606

US

Cage: LO508

Ingredients

METHYL N-BUTYL KETONE (2-HEXANONE)

CAS: 591-78-6

RTECS: MP1400000

Fraction By Weight: 5%

OSHA PEL100 PPM

ACGIH TLV: S, 5 PPM; 9293

2-ETHOXYETHANOL (EGEE) (SARA III)

CAS: 110-80-5

RTECS: KK8050000

Fraction By Weight: 5%

OSHA PELS,200 PPM

ACGIH TLV: S, 5 PPM; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TRI METHYLOL PHENOL

Fraction By Weight: 1%

PIGMENTS

Fraction By Weight: 68%

VEHICLE

Fraction By Weight: 21%

Hazards

Effects of Overexposure: INHAL: HEADACHE, NAUSEA, DIZZINESS. SKIN: REPEATED/PROLONGED CONTACT MAY CAUSE IRRITATION.

First Aid

First Aid: INHAL: REMOVE TO FRESH AIR. SKIN: FLUSH WITH LARGE AMTS WATER & REMOVE CONTAMINATED CLOTHING. EYE: FLUSH WITH CLEAN WATER 15 MIN & CALL PHYSICIAN.

Fire Fighting

Flash Point: 77F (PMCC)

Lower Limits: 1.2

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL

Unusual Fire/Explosion Hazard: WATER SHOULD BE USED TO COOL CONTAINERS EXPOSED TO FIRE

Accidental Release

Spill Release Procedures: AVOID BREATHING VAPORS, EXTINGUISH IGNITION SOURCES IN IMMEDIATE AREA. AVOID CONTACT WITH LIQUID.

Handling

Handling and Storage Precautions: DO NOT STORE AT ELEVATED TEMPERATURES

Other Precautions: CLOSE CONTAINERS AFTER USE

Exposure Controls

Respiratory Protection: BU MINES APPR RESPIRATOR IN CONFINED AREAS

Ventilation: ADEQUATE TO KEEP VAPOR CONCENTRATION LOW. USE SPARK-PROOF FAN

Protective Gloves: VINYL

Eye Protection: SOLVENT RESISTANT

Other Protective Equipment: NORMAL PROTECTIVE CLOTHING

Supplemental Safety and Health

KEY1: F4.

Chemical Properties

HCC: F3

Boiling Pt: B.P. Text: 200-260F

Spec Gravity: 2.04

Appearance and Odor: GRAY MOBILE LIQUID

Percent Volatiles by Volume: 26

Stability

Stability Indicator/Materials to Avoid: YES

OXIDIZERS; SOFTENS RUBBER

Hazardous Decomposition Products: CARBON MONOXIDE; CARBON DIOXIDE

Disposal

Waste Disposal Methods: DISPOSE OF IN CLOSED CONTAINERS AWAY FROM IGNITION SOURCES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.