

M.C.GREEN;742-408;ENAMEL ALKYD GLOSS

MSDS Number

BFCMF

National Stock Number

8010-00-526-1607

Product Name

M.C.GREEN;742-408;ENAMEL ALKYD GLOSS

Manufacturer

ENMAR AN AMERON CO

Product Identification

Product ID:M.C.GREEN;742-408;ENAMEL ALKYD GLOSS

MSDS Date:01/01/1987

FSC:8010

NIIN:00-526-1607

MSDS Number: BFCMF

Responsible Party

ENMAR AN AMERON CO

Emergency Phone: (316)733-1361

Cage: JO877

Contractor

ENMAR AN AMERON COMPANY

BREA, CA 92621-3904

US

714-529-4597

Cage: JO877

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 49.4%

OSHA PEL100 PPM

Hazards

Effects of Overexposure:INH:ANESTHETIC, IRRIT OF RESP TRACT OR ACUTE
CNS DEPRSSN W/HDACHE,DIZ,UNCON,COMA. SKIN & EYE: IRRIT

First Aid

First Aid:IN CASE OF CONTACT, FLUS SKIN & EYES W/PLENTY OF WATER WHILE
REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR.
CALL A PHYSICIAN IF SYMPTOMS PERSIST.

Fire Fighting

Flash Point:104F TCC

Lower Limits:1.1

Extinguishing Media:SM FIRES:CO*2,DRY CHEM. LG FIRES:POLYMER FOAM
PREFERRED.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD-UP.

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAME, HOT SURFACES, & ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE W/ INERT ABSORBENT & NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120°F. STORE LG QTY IN BUILDINGS DESIGNED TO STORE NFPA CLASS ONE FLAM LIQ. DO NOT TAKE INTERNALLY. ADD LABEL WARNING.

Other Precautions: GROUND CONTAINERS WHEN POURING. AVOID FREE FALL OF LIQ IN EXCESS OF FEW IN. DO NOT FLAME CUT, BRAZE OR WELD COATED MATERIAL W/O APPROVED RESPIRATOR OR APPROPRIATE VENTILATION. DOT: FLAM LIQUID.

Exposure Controls

Respiratory Protection: RESTRICT VENT: CHEM-MECH FLTR. CLSD: AIR-LINE TYPE
Ventilation: GEN DILTN/LOCAL EXHST TO KEEP TLV/LEL BELOW LIMIT, REMV FUME

Protective Gloves: YES

Eye Protection: YES, FOR SPLASH

Other Protective Equipment: AVOID LONG EXPOSURE TO CONTAM CLOTHING

Supplemental Safety and Health

VAPOR PRESSURE: 3.2; VAPOR DENSITY: HEAVIER THAN AIR; WT PER GALLON 8.2 LBS.

Chemical Properties

HCC: F4

Boiling Pt: B.P. Text: 311-373°F

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 63.2

Stability

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: AVOID FIRES, HEAT & HOT SURFACES

Disposal

Waste Disposal Methods: DO NOT INCINERATE CLOSED CONTAINER. DISPOSE IN ACCORDANCE W/ FED., STATE & LOCA REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.