

## **13538-YELLOW**

### **MSDS Number**

BFCQX

### **National Stock Number**

8010-00-527-2045

### **Product Name**

13538-YELLOW

### **Manufacturer**

PRATT AND LAMBERT

### **Product Identification**

Product ID:13538-YELLOW

MSDS Date:01/01/1985

FSC:8010

NIIN:00-527-2045

MSDS Number: BFCQX

### **Responsible Party**

PRATT & LAMBERT

Emergency Phone: 316-733-1361

Cage: PRATT

### **Contractor**

PRATT AND LAMBERT INC

2153

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

### **Ingredients**

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 35%

ACGIH TLV: 500 PPM

MED CHROME YELLOW

RTECS: GB1225000

Fraction By Weight: 25%

ACGIH TLV: >10.000 G/KG

LEAD NAPHTHENATE 362

Fraction By Weight:

ACGIH TLV: 0.500 G/KG

TRIETHYLAMINE (SARA III)

CAS: 121-44-8

RTECS: YE0175000

Fraction By Weight:

OSHA PEL25 PPM/15 STEL

ACGIH TLV: 10 PPM/15 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

MOLYBDATE ORANGE

CAS: 12656-85-8

RTECS: QA4660000

Fraction By Weight:

ACGIH TLV: >10.000 G/KG

## Hazards

Effects of Overexposure: IRRIT OF NOSE, THROAT, EYES & POSS DIZZINESS & NAUSEA. SPRAY MIST CONTN LEAD.

## First Aid

First Aid: INHAL: REMOVE FR EXPOSURE & PROVID FRESH AIR. SPLASH EYES- FLUSH IMMEDIATE W/ LG AMTS OF WATER FOR 15 MIN. SPLASH SKIN: REMOVE CONTAM CLOTHING & WASH ALL AFFECTED AREA W/ WATER. INGEST: DO NOT INDUCE VOMITING. CONSULT A DR . IMMEDIATE IN ALL CASES.

## Fire Fighting

Flash Point: 104 F 40 C TCC

Extinguishing Media: CLASS B EXTING, CARBON DIOXIDE, DRY CHEM OR ALCOHOL FOAM

Fire Fighting Procedures: SELF CONTAINED BREATH APPARATUS WATER MAY BE INEFFECTIVE.

Unusual Fire/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS & OPEN FLAME. DO NOT APPLY TO VERY HOT SUR

## Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, ELECTRICAL, STATIC OR FRICTIONAL SPARKS). VENTILATE AREA & AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT & NON-SPARKING TOOLS. STEPS MUST BE TAKEN TO PREVENT CONTAMINATION OF GROUND WATER OR STREAMS.

## Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120 F. STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 1910.106. CONTAINERS SHOULD BE GROUNDING & BONDED TO THE RECEIVING CONTAINER.

Other Precautions: DO NOT CUT OR WELD ON EMPTY CONTAINER. DO NOT USE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER.

## Exposure Controls

Respiratory Protection: NIOSH APPROVED MECHANICAL RESPIRATOR TO REMOVE OVERSPRAY WHEN SPRAYING IN OUTDOOR

Ventilation: PROVIDE GENERAL DILUTION/LOCAL EXHAUST VENT TO KEEP CONCENTRATION BELOW ACCEPTABLE

Protective Gloves: SOLVENT, IMPERMEABLE

Eye Protection: SAFETY EYEWEAR

Other Protective Equipment: PROTECTIVE EQUIPMENT TO PREVENT SKIN CONTACT. SEE

OSHA, 29 CFR 1910.1025

Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:311-373F

Vapor Density:>AIR

Evaporation Rate & Reference:Percent Volatiles by Volume:59

## Stability

Stability Indicator/Materials to Avoid:YES

AVOID CONTCT W.STRONG ACIDS OR AKALINE MATERIALS.

Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES.

Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE & OXIDES OF CARBON & LEAD.

Conditions to Avoid Polymerization:DO NOT ADD DRIERS OR REACTIV CHEM W/O TECHN SUPERVISION.

## Disposal

Waste Disposal Methods:DISPOSE IN ACCORD W/LOCAL, STATE & FEDERAL REGULATIONS.INCINERATIN EPA APPRVD FACILITY.DO NOT INCINERAT CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.