

GLOSS YELLOW 13538

MSDS Number

BFCRB

National Stock Number

8010-00-527-2045

Product Name

GLOSS YELLOW 13538

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID:GLOSS YELLOW 13538

MSDS Date:01/01/1985

FSC:8010

NIIN:00-527-2045

MSDS Number: BFCRB

Responsible Party

PRATT AND LAMBERT INC

945 BURLINGTON

KANSAS CITY , MO 64141

US

Cage: 92216

Contractor

PRATT AND LAMBERT INC

206

KANSAS CITY, MO 64141

US

Cage: 92216

Ingredients

LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR

CAS: 7758-97-6

RTECS: GB2975000

Fraction By Weight: 20-3%

OSHA PEL0.05 MG/M3 (PB)

ACGIH TLV: 0.05MG/M3(CR)A2;8990

TRIETHYLAMINE (SARA III)

CAS: 121-44-8

RTECS: YE0175000

Fraction By Weight:

OSHA PEL25 PPM/15 STEL

ACGIH TLV: 10 PPM/15 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 30-4%

OSHA PEL100 PPM

LEAD NAPHTHENATE 36% LD 50 VALUE @ .500 GMS/KG

RTECS: OG2025000

Fraction By Weight:

Hazards

Effects of Overexposure:INHALATION:ANESTHETIC,IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION CHARACT

First Aid

First Aid:IN CASE OF CONTACT,FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED,REMOVE TO FRESH AIR.CALL A DR. IF SYMPTOMS PERSIST.SKIN OR EYE CONTACT:PRIMARY IRRITATION.

Fire Fighting

Flash Point:104 F TCC

Lower Limits:1.10

Extinguishing Media:USE NATIONAL FIRE PROTECTION ASSOC.(NFPA) CLASS B EXTINGUI

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS SHOULD BE AUAILABLE FOR

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED.ISOLATE FROM HEAT,ELECTRICAL EQUIPMENT,SPARKS AND OPEN FLAME. CLOSED

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT SURFACES,AND ELECTRICAL,STATIC,OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DO NOT STORE 120F. STORE LARGE QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING.AVOID FREE FALL OR LIQUID IN EXCESS OF A FEW INCHES.DO NOT FLAME CUT,BRAZE OR WELD COATED MATERIAL WITH BUREAU OF MINES APPROVED RESPIRATOR OR APPRO

Exposure Controls

Respiratory Protection:IN OUTDOOR OR OPEN AREAS,USE BUREAU OF MINES APPROVED MECHANICAL FIL

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION.IN VOL

Protective Gloves:REQUIRED FOR PR

Eye Protection:USE SAFETY EYEWEAR.DESI

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.

Supplemental Safety and Health

INHALATION:ANESTHETIC,IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY HEADACHE,DIZZINESS,STAGGERING GAIT,CONFUSION,UNCONSCIOUSNESS OR COMA.

Chemical Properties

HCC:F4

Stability

Stability Indicator/Materials to Avoid: YES

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.