

## **BLACK #17038**

### **MSDS Number**

BFCRC

### **National Stock Number**

8010-00-527-2050

### **Product Name**

BLACK #17038

### **Manufacturer**

AMERON INDUSTRIAL COATINGS DIV

### **Product Identification**

Product ID:BLACK #17038

MSDS Date:01/01/1987

FSC:8010

NIIN:00-527-2050

MSDS Number: BFCRC

### **Responsible Party**

AMERON INDUSTRIAL COATINGS DIVISION

Emergency Phone: 316-7331361

Cage: 09869

### **Contractor**

AMERON INDUSTRIAL COATINGS DIVISION

BREA, CA 92621-3904

US

714-529-4597

Cage: 09869

### **Ingredients**

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 53.0%

OSHA PEL100 PPM

### **Hazards**

Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE  
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

### **First Aid**

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE  
TO FRESH AIR. CALL A PHYSICIAN IF CONDITIONS PERSIST.

### **Fire Fighting**

Flash Point:85F TCC

Lower Limits:1.1

Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE  
FIRES-FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE

### **Accidental Release**

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS

## Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120°F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE

Other Precautions: CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES

## Exposure Controls

Respiratory Protection: USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation: PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY

Supplemental Safety and Health

RESPIRATOR USE BASED ON CHEM. CONC. AND CONDITIONS OF USE.

## Chemical Properties

HCC: F4

Boiling Pt: B.P. Text: 311-373°F

Vapor Density: > 1

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 64.3

## Stability

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: AVOID FIRE, HEAT AND HOT SURFACES

## Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.