

ENAMEL ALKYD GLOSS BLACK 17038

MSDS Number

BFCRD

National Stock Number

8010-00-527-2050

Product Name

ENAMEL ALKYD GLOSS BLACK 17038

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID:ENAMEL ALKYD GLOSS BLACK 17038

MSDS Date:01/01/1987

FSC:8010

NIIN:00-527-2050

MSDS Number: BFCRD

Responsible Party

PRATT AND LAMBERT INC

16116 E 13TH ST

WICHITA , KS 67201

US

Emergency Phone: 716-873-6000 DOT EMER 8002553924

Info Phone: 316-733-1361

Cage: 61196

Contractor

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

*MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

CARBON BLACK

CAS: 1333-86-4

RTECS: FF5800000

OSHA PEL3.5 MG/M3

ACGIH TLV: 3.5 MG/M3; 9192

Hazards

Effects of Overexposure:MAY CAUS GASTRO IRRIT,RESPIRAT IRRIT.CARBON BLK IS LISTED AS A POTENTL CARCINOGEN.UNCONSC,ASPHYXIAT

First Aid

First Aid:IF SWALLOW:INDUC VOMIT IMMED BY GIVNG 2 GLASSES OF WATR & STIKING FINGR DOWN THROAT.CONSULT DR.OR POISON CONTROL CENTR IMMED.(NVR GIVE ANYTHING BY MOUTH TO AN UNCONSC PERSON.)INHAL:REMOV TO FRESH AIR IMMED.IF BREATHNG STOP,GIVE ARTIFICIAL RESPIRATION

Fire Fighting

Flash Point:80F 27C

Extinguishing Media:CL B FIRE EXTING CO*2,ALL PURPOS DRY CHEM/ALCOH FOAM

Fire Fighting Procedures:FIREFIGHTRS SHLD WR SELF-CONTND BREATHNG APPARATUS.

Unusual Fire/Explosion Hazard:KEEP CONTNRS TIGHTLY CLOS.ISOLAT FR HEAT,ELECTR EQPMT,SPARKS & FLAME.CLOS CONTRS MAY EXPLOD WHN(SUP)

Accidental Release

Spill Release Procedures:KEEP SPECTATORS AWAY.ELIMINATE ALL IGNIT SOURCES(FLAMES,HOT SURFACES & SOURCES OF ELECTR,STATIC OR FRICTIONAL SPARKS).DIKE & CONTN SPILL W/INERT MATERIAL (E.G.SAND,EARTH).TRANSFR LIQDS TO COVRD METAL CONTNRS F/RECOVERY OR DISPOSAL OR REMOVW/INERT

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG QUANTITIES IN COMPLIANCE W/OSHA 29CFR1910.106.

Other Precautions:DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE.

Exposure Controls

Ventilation:PROVIDE GEN DILUT & LOC EXHAUST VENTIL IN SUFFICIENT VOLUME.

Protective Gloves:SOLVNT IMPERMEA

Eye Protection:SAFETY SPECTACLES W/SIDE

Other Protective Equipment:NOT LIKELY TO BE NEEDED

Supplemental Safety and Health

*INDICATES SOLVENT. UNUS FIRE/EXPLOS HAZ:EXPOSED TO EXTREME HEAT.

Chemical Properties

HCC:F3

Boiling Pt:B.P. Text:244-399F

Vapor Density:HEAV

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:62

Stability

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS

Hazardous Decomposition Products:BURNING,HEAT BY WELD/CUTTNG W/PRODUC SMOKE,CARBON MONOXID,CA

Disposal

Waste Disposal Methods:DISPOSE IN ACCORD W/FEDERAL,STATE & LOCAL LAWS. INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED

CONTNRS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.