

## **792-410**

### **MSDS Number**

BFCFSF

### **National Stock Number**

8010-00-527-2479

### **Product Name**

792-410

### **Manufacturer**

AMERON INDUSTRIAL COATINGS DIV PRATT AND LAMBERT

### **Product Identification**

Product ID:792-410

MSDS Date:01/01/1985

FSC:8010

NIIN:00-527-2479

MSDS Number: BFCFSF

### **Responsible Party**

AMERON INDUSTRIAL COATINGS DIV,PRATT AND LAMBERT

Emergency Phone: 316-733-1361

Cage: 09869

### **Contractor**

AMERON INDUSTRIAL COATINGS DIVISION

BREA, CA 92621-3904

US

714-529-4597

Cage: 09869

### **Ingredients**

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

OSHA PEL100 PPM/75 STEL  
ACGIH TLV: 50 PPM/75 STEL; 9293  
EPA Report Quantity: 5000 LBS  
DOT Report Quantity: 5000 LBS

ISOBUTYL ACETATE  
RTECS: AL1402500  
ACGIH TLV: 150 PPM

TOLUENE (SARA III)  
CAS: 108-88-3  
RTECS: XS5250000  
OSHA PEL200 PPM/150 STEL  
ACGIH TLV: 50 PPM; 9293  
EPA Report Quantity: 1000 LBS  
DOT Report Quantity: 1000 LBS

## Hazards

Effects of Overexposure:EYE,THROAT,SKIN,LUNG  
IRRITANT;DEPRESSANT;COMA;UNCONSCIOUSNESS;DIZZINESS.

## First Aid

First Aid:SKIN:WASH WELL. EYES:FLUSH WITH WATER. INHAL:REMOVE TO FRESH  
AIR.GIVE ARTIF.RESP.IF NEEDED,CALL DR. REMOVE CONTAMINATED  
CLOTHING.

## Fire Fighting

Flash Point:28F,-2.2C TCC  
Lower Limits:1.2  
Extinguishing Media:FOAM,DRY CHEM.,CARBON DIOXIDE  
Fire Fighting Procedures:CLOSED CONTAINERS MAY BURST WHEN EXPOSED TO  
HEAT  
Unusual Fire/Explosion Hazard:AVOID FIRE,HEAT,SPARKS,IGNITION  
SOURCES,STORAGE IN DIRECT SUNLIGHT.

## Accidental Release

Spill Release Procedures:VENTILATE AREA MECHANICALLY,KEEP FROM  
FLAME,FIRE,SPARKS,IGNITION SOURCES;DO NOT BREATHE VAPORS;CLEAN UP  
WITH ABSORBENT MATERIAL;USE NON-SPARKING TOOLS

## Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED,UPRIGHT,AWAY  
FROM FIRE,FLAME,SPARKS,IGNITION SOURCES,DIRECT SUNLIGHT; DO NOT  
SOTRE ABOVE 120F;STORAGE NFPA CLASS I FLAMMABLE.  
Other Precautions:DO NOT INGEST.GROUND WHEN POURING.DO NOT FLAME  
CUT,BRAZE,OR WELD COATED MATERIAL W/O ADEQUATE VENTILATION OR  
BUREAU OF MINES APPROVED RESPIRATOR.

## Exposure Controls

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN  
Ventilation:LOCAL EXHAUST,MECHANICAL  
Protective Gloves:YES  
Eye Protection:GOGGLES/SAFETY GLASSES  
Supplemental Safety and Health  
BOILING RANGE IS 174-243F

## Chemical Properties

HCC:F2  
Boiling Pt:B.P. Text:174F,78C  
Appearance and Odor:LIQUID,COLOR-OLIVE DRAB  
Percent Volatiles by Volume:74.0

## **Stability**

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:FIRES,HEAT,HOT SURFACES

## **Disposal**

Waste Disposal Methods:LOCAL,STATE,AND NATIONAL LAWS;DO NOT INCINERATE  
CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.