

791202 LACQUER-ACRYLIC N/C

MSDS Number

BFCTK

National Stock Number

8010-00-527-2502

Product Name

791202 LACQUER-ACRYLIC N/C

Manufacturer

PRATT AND LAMBERT WICHITA DIV

Product Identification

Product ID: 791202 LACQUER-ACRYLIC N/C

MSDS Date: 01/01/1985

FSC: 8010

NIIN: 00-527-2502

MSDS Number: BFCTK

Responsible Party

PRATT & LAMBERT-WICHITA DIV.

16116 E 13TH ST

WICHITA , KS 67201

US

Cage: KO010

Contractor

PRATT AND LAMBERT INC

2153

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

MOLYBDATE ORANGE LD 50

CAS: 12656-85-8

RTECS: QA4660000

Fraction By Weight: 15%

ISOBUTYL ACETATE

RTECS: NP9100000

METHYL ISOBUTYL KETONE (HEXONE) (SARA III)

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight:

OSHA PEL100 PPM

ACGIH TLV: 50 PPM/75 STEL; 9394

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

CYCLOHEXANE (SARA III)

CAS: 110-82-7

RTECS: GU6300000

Fraction By Weight: 8%

OSHA PEL300 PPM

ACGIH TLV: 300 PPM, 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 8%

OSHA PEL100 PPM

Hazards

Effects of Overexposure: INHAL: ANEST, IRRIT OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION, HEADACHE, DIZZINESS, CONFUSION, UNCONSCIOUSNESS, COMA

First Aid

First Aid: IN CASE OF CONTACT, FLUSH SKIN/EYES WITH PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, MOVE TO FRESH AIR. CALL A PHYSICIAN. IF SYMPTOMS PERSIST.

Fire Fighting

Flash Point: 50°F TCC 10°C

Lower Limits: .90

Extinguishing Media: NFPA CL B EXTING (CO₂, DRY CHEM OR ALCOHOL FOAM).

Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIREMEN.

Unusual Fire/Explosion Hazard: KEEP CONTAINER TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRIC EQUIPMENT, SPARKS & OPEN FLAME. CLOSURE OF CONTAINER MAY EXPLODE WHEN (SU)

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, & ELECTRIC, STATIC, OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT & NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120°F. STORE LARGE QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106.

Other Precautions: CONTAINERS GROUNDED WHEN POURING. AVOID FORTH FALL OF LIQUID IN EXCESS OF A FEW INCHES. DO NOT FLAME CUT, BRAZE OR WELD COATED MATERIAL WITHOUT BUR OF MINES APPROVED RESPIRATOR OR APPROPRIATE VENTILATION. ADD LABEL WARNING. DO NOT TAP

Exposure Controls

Respiratory Protection: OUTDOOR/OPEN AREAS, USE BUR OF MINES APPROVED MECHANICAL FILTER RESPIRATOR.

Ventilation: PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME TO KEEP BELOW TOLERABLE LIMIT.

Protective Gloves: REQUIRED FOR REPEATED

Eye Protection: SAFETY EYEWEAR.

Other Protective Equipment:PREVNT PROLNG SKIN CONTACT TO CONTAMINATED CLOTHING.
Supplemental Safety and Health
UNUS.FIRE & EXPLOS: EXPOSED TO EXTREME HEAT. DO NOT APPLY TO VERY HOT SURFACES.

Chemical Properties

HCC:F2
Boiling Pt:B.P. Text:175-321F
Vapor Density:HEAV
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:72

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID FIRES,HEAT, & HOT SURFACES.

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOC STAATE,& FEDERAL REGULATIONS. INCINERATE IN APPRVD FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.