

## **79310 LAC SPRAYING YELLOW 13538**

### **MSDS Number**

BFCVK

### **National Stock Number**

8010-00-527-2624

### **Product Name**

79310 LAC SPRAYING YELLOW 13538

### **Manufacturer**

PRATT AND LAMBERT WICHITA DIV

### **Product Identification**

Product ID:79310 LAC SPRAYING YELLOW 13538

MSDS Date:01/01/1985

FSC:8010

NIIN:00-527-2624

MSDS Number: BFCVK

### **Responsible Party**

PRATT & LAMBERT-WICHITA DIV

16116 E 13TH ST

WICHITA , KS 67201

US

Cage: KO010

### **Contractor**

PRATT AND LAMBERT INC

2153

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

### **Ingredients**

ISOBUTYL ACETATE

RTECS: NP9100000

Fraction By Weight: 35%

ACGIH TLV: 150PPM

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

Fraction By Weight: 8%

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 15%

OSHA PEL200 PPM

ACGIH TLV: 200 PPM/300STEL;9394

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 8%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

NAPHTHA ALIPHATIC

## Hazards

Effects of Overexposure: ANEST, IRRIT OF RESPIR TRACT OR ACUT NERV SYS  
DEPRESN, HDACH, DIZZ, CONFUS, UNCONSCIOUS, COMA.

## First Aid

First Aid: IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE  
REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOV TO FRESH AIR. CALL A  
PHYSICIAN IF SYMPTOMS PERSIST.

## Fire Fighting

Flash Point: 13F TCC - 11C

Lower Limits: .90

Extinguishing Media: USE FIRE EXTING(CO\*2, DRY CHEM OR ALCOH FOAM) LO  
FIRE-POLYMER

Fire Fighting Procedures: SELF-CONTAINED BREATH APPARATUS SHLD BE AVAIL  
F/FIREMEN.

Unusual Fire/Explosion Hazard: KEEP CONTNRS TIGHTLY CLOS: ISOLAT FR  
HEAT, ELECTR EQPMT. SPARKS & OPEN FLAME. CLOS CONTNRS MAY EXPLO(SUP

## Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT  
SURFACES, & ELECTRICAL, STATIC OR FRICTIONAL SPARKS) AVOID BREATHING  
VAPORS. VENTILAT AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

## Handling

Handling and Storage Precautions: DO NOT STORE ABOV 120F. STORE LG  
QUANTITIES IN BLDB DESIGNED TO COMPLY W/OSHA 1910.106.

Other Precautions: CONTNRS GROUNDED WHEN POURING AVD FIRE FAL OF LIQD IN  
EXCESS OF FEW INCHES. DON'T FLAM CUT, BRAZE OR WELD COATED MATRL W/O  
BUR OF MNES APPRVD RESPIR OR APPROP VENT. AD LABL WARN "DONOT TAKE  
INTERN

## Exposure Controls

Respiratory Protection: OUTDOOR/OPEN AREAS, USE BUR. OF MINES APPRVD MECH  
FILTR RESPIRATOR.

Ventilation:PROVID GEN DILUT OR LOC EXHAUST VENT IN VOL TO KP BELOW TLV.  
Protective Gloves:F/REPTD CONTACT  
Eye Protection:SAFETY EYEWEAR  
Other Protective Equipment:PRVNT PROLONG SKIN CONTACT TO CONTAMINATED CLOTHING.  
Supplemental Safety and Health  
UNUS FIRE & EXPOS HAZ:WHEN EXPOSED TO EXTREME HEAT.DO NOT APPLY TO VERY HOT SURFACES.

## **Chemical Properties**

HCC:F2  
Boiling Pt:B.P. Text:174-290F  
Vapor Density:HEAV  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:77

## **Stability**

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:AVOID FIRES,HEAT & HOT SURFACES

## **Disposal**

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOC,STATE & FEDERAL REGULATIONS.INCINERATE IN APPRVD FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.