

TT-E-508,#24672,SEMI-GLOSS ALKYD ENAMEL

MSDS Number

BFCVY

National Stock Number

8010-00-527-2634

Product Name

TT-E-508,#24672,SEMI-GLOSS ALKYD ENAMEL

Manufacturer

PRESERVATIVE PAINT COMPANY

Product Identification

Product ID:TT-E-508,#24672,SEMI-GLOSS ALKYD ENAMEL

MSDS Date:01/01/1987

FSC:8010

NIIN:00-527-2634

MSDS Number: BFCVY

Responsible Party

PRESERVATIVE PAINT COMPANY

Emergency Phone: (206)634-5252

Cage: 86589

Contractor

PRESERVATIVE PAINT CO

80387

SEATTLE, WA 98108-1726

US

Cage: 86589

Ingredients

PIGMENTS(TYPE NOT SPECIFIED)

Fraction By Weight: 47%

ALKYD SOLIDS (AS VEHICLE)

Fraction By Weight: 25%.

STANDARD OIL 350B (INCLUDES 27.2% PARAFFINS(INCL.

Fraction By Weight: 28%.

ACGIH TLV: 250 PPM-MFG

Hazards

Effects of Overexposure:INHAL OF HIGH VAPOR CONCS OR MISTS MAY LEAD TO ASPHYXIATION.PROMPT REMOVA TO FRESH AIR IS IMPORTANT

First Aid

First Aid:SKIN:WASH THOROUGHLY W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING & WASH BEFORE REUSE.EYES:IMMEDIATELY FLUSH W/WATER AT LEAST 15 MINS. CALL MD. INGESTION:DO NOT INDUCE VOMITING CALL MD.INHAL:REMOVE TO FRESH AIR IMMEDIATELY.

Fire Fighting

Flash Point:104F TCC
Lower Limits:0.8
Upper Limits:6.8
Extinguishing Media:CO*2, DRY CHEMICAL
Fire Fighting Procedures:ELIMINATE ALL SOURCES OF IGNITION

Accidental Release

Spill Release Procedures:EXTINGUISH ALL SOURCES OF IGNITION IN VICINITY OF SPILL OR RELEASED VAPORS.CLEAN UP SPILLS AS SOON AS POSSIBLE.ABSORB LARGE SPILLS W/CLAY OR DIATOMACEOUS EARTH

Handling

Handling and Storage Precautions:STORE IN COOL, WELL-VETILATED AREA AWAY FROM SOURCES OF IGNITION.CONTAINERS SHOULD HAVE A FLAMMABLE LIQUID "CAUTION"LABEL.

Exposure Controls

Respiratory Protection:ORGANIC VAPOR RESP;SELF-CONTAINED APPRTS IF VAPOR CONC > TLV
Ventilation:LOCAL EXHAUST IF VAPOR CONCENTRATIONS EXCESSIVE
Protective Gloves:NEOPRENE/RUBBER
Eye Protection:CHEM. SFTY GOGGS IF SPLSH
Supplemental Safety and Health
VAPOR PRESSURE:0.3 MMHG.MFG SUGGESTS TLV OF 250 PPM

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:311 TO 386F
Vapor Density:4.8
Spec Gravity:1.38
Evaporation Rate & Reference:0.12 BUTYL ACETATE
Solubility in Water:NEGLIGIBLE
Percent Volatiles by Volume:48.0

Stability

Stability Indicator/Materials to Avoid:YES
MAY REACT WITH STRONG OXIDIZING MATERIALS
Hazardous Decomposition Products:NRML CMBSTN-CO*2, WATER
VAPOR;INCOMP.CMBSTN-CO

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL, STATE & FED CODES

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.