

## **ENAMEL ALKYD SG GREEN 24533 (745468)**

### **MSDS Number**

BFCXP

### **National Stock Number**

8010-00-527-3197

### **Product Name**

ENAMEL ALKYD SG GREEN 24533 (745468)

### **Manufacturer**

PRATT AND LAMBERT

### **Product Identification**

Product ID:ENAMEL ALKYD SG GREEN 24533 (745468)

MSDS Date:01/01/1987

FSC:8010

NIIN:00-527-3197

MSDS Number: BFCXP

### **Responsible Party**

PRATT & LAMBERT

16116 E 13TH ST

WICHITA , KS 67201

US

Cage: PRATT

### **Contractor**

PRATT AND LAMBERT INC

2153

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

### **Ingredients**

SILICA, CRYSTALLINE - CRISTOBALITE

CAS: 14464-46-1

RTECS: VV7325000

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.05 MG/M3 RDUST9293

LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR

CAS: 7758-97-6

RTECS: GB2975000

OSHA PEL0.05 MG/M3 (PB)

ACGIH TLV: 0.05MG/M3(CR)A2;8990

TALC (CONTAINING NO ASBESTOS)

CAS: 14807-96-6

RTECS: WW2710000

OSHA PEL2 MG/M3 RDUST

ACGIH TLV: 2 MG/M3 RDUST; 9192

TITANIUM DIOXIDE

RTECS: XR2100000

ACGIH TLV: 10 MG/CU.M.

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

## Hazards

Effects of Overexposure:SWALLOWING CAN CAUSE  
VOMITING.INHALATION-ANESTHETIC,HEADACHE,DIZZINESS.EYE-MAY CAUSE  
IRRITATION.

## First Aid

First Aid:IF SWALLOWED INDUCE VOMITING.CONSULT PHYSICIAN OR POISON  
CONTROL CENTER.INHALATION-REMOVE TO FRESH AIR.EYE-FLUSH WITH LARGE  
AMOUNTS OF WATER FOR 15 MINUTES.SKIN-WASH WITH SOAP AND WATER.GET  
MEDICAL AT TENTION IF IRRITATION PERSISTS.

## Fire Fighting

Flash Point:80F(26.67C)

Extinguishing Media:CLASS B FIRE EXTINGUISHERS

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED.ISOLATE  
FROM HEAT

## Accidental Release

Spill Release Procedures:KEEP SPECTATORS AWAY.ELIMINATE ALL IGNITION  
SOURCES.DIKE AND CONTAIN SPILL WITH INERT MATERIAL.TRANSFER LIQUIDS  
TO COVERED METAL CONTAINERS FOR RECOVERY OR DISPOSAL.PREVENT  
CONTAMINATION OF SEWERS,STR EAMS AND GROUND WATER WITH SPILLED  
MATERIAL.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE  
QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106

Other Precautions:DO NOT TAKE INTERNALLY.CLOSE CONTAINER AFTER USE.DO  
NOT BREATHE SANDING DUST.EMPTY CONTAINERS MUST NOT BE WASHED AND  
REUSED.NEVER USE PRESSURE TO EMPTY CONTAINER.

## Exposure Controls

Respiratory Protection:NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY  
WHN SPRAYING IN OUTDR

Ventilation:PROVIDE GENERAL DILUTION AND LOCAL EXHAUST VENTILATION

Protective Gloves:IMPERMEABLE

Eye Protection:GOGGLES AND FACE SHIELD

Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT

Supplemental Safety and Health

## Chemical Properties

Boiling Pt:B.P. Text:148F  
Vapor Pres:5  
Vapor Density:>1  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:55

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG ACIDS OR ALKALINE MATERIALS  
Stability Condition to Avoid:NONE KNOWN  
Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE,CARBON MONOXIDE AND DIOXIDE

## Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL LAWS.INCINERATE ONLY IN EPA PERMITTED FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIALS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.