

745442 ENAMEL ALKYD SG GREEN 24410

MSDS Number

BFDBQ

National Stock Number

8010-00-530-5556

Product Name

745442 ENAMEL ALKYD SG GREEN 24410

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID:745442 ENAMEL ALKYD SG GREEN 24410

MSDS Date:01/01/1985

FSC:8010

NIIN:00-530-5556

MSDS Number: BFDBQ

Responsible Party

PRATT AND LAMBERT INC

16116 E 13TH ST

WICHITA , KS 67201

US

Emergency Phone: 716-873-6000 DOT EMER 8002553924

Info Phone: 316-733-1361

Cage: 61196

Contractor

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight:

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 35%

ACGIH TLV: 500 PPM

LEAD NAPHTHENATE 36% LD 50 VALUE= .500 GMS/KG

Fraction By Weight:

DIETHYLENE TRIAMINE

CAS: 111-40-0

RTECS: IE1225000

OSHA PEL1 PPM

ACGIH TLV: S, 1 PPM; 9192

LEAD CHROMATE PIGMENT LD 50 VALUE>10.000 GMS/KG.

Fraction By Weight:

Hazards

Effects of Overexposure:INHAL:ANEST IRRITATION OF RESPIRATORY TRACT OR ACUT NERV SYS DEPRSSN,HDACH,DIZZ,CONFUSN,UNCON,COMA.

First Aid

First Aid:IN CASE OF CONTCT,FLUSH SKIN & EYES W/PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING.IF INHALED, REMOVE TO FRESH AIR. CALL A DR IF SYMPTOMS PERSIST.

Fire Fighting

Flash Point:104F TCC 40C

Extinguishing Media:CO*2,DRY CHEM OR ALCOHOL FOAM.POLYMR RECMMD F/LG FIRES

Fire Fighting Procedures:SELF-CONTND BREATHING APPARAT WATR SPRAY MAY BE INEFFECTIVE

Unusual Fire/Explosion Hazard:KP CONTNRS TIGHTLY CLOS.ISOLAT FR HEAT,ELECTR EQUIPMT,SPARKS & OPN FLAME.CLOS CONTNRS MAY EXPLOD(SUP

Accidental Release

Spill Release Procedures:REMOV ALL SOURCES OF IGNITION (FLAMES,HOT SURFACES, & ELECTRICAL,STATIC, OR FRICTIONAL SPARKS).AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG QUANTITIES IN BLDG DESIGNED TO COMPLY W/OSHA 1910.106.

Other Precautions:CONTNRS SHLD BE GRNDED WHN POURNG.AVD FRE FAL OF LIQD IN EXCES OF FEW INCH.DO NOT FLAME CUT,BRAZ,WELD COATED MATRL W/O BUR MNES APRVD RESPIRAT OR APPROP VENT.AD WARN LABL-DO NOT TAKE INTERNALL

Exposure Controls

Respiratory Protection:MECH FILTR RESPIRAT TO REMOV SOLID AIR BORNE PARTICL/OVERSPRAY INDOR

Ventilation:LOC EXHAUS VENTIL TO KP TLV OF HAZARD INGRED BELO ACCEP LIMT

Protective Gloves:F/PRLNG/REPEAT

Eye Protection:SAFTY EYEWK PROTECT AGNST

Other Protective Equipment:PREVNT PRLNG SKN CONTD TO CONTAMINATED CLOTHING.

Supplemental Safety and Health

UNUS. FIRE/EXPLOS HAZARDS:WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO VERY HOT SURFACES.

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:311-373F
Vapor Density:HEAV
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:57

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID FIRES,HEAT, & HOT SURFACES.

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL,STATE & FEDERAL REGULATIONS. INCINERATE IN APPRVD FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.