

24518-GREEN

MSDS Number

BFDCF

National Stock Number

8010-00-530-5567

Product Name

24518-GREEN

Manufacturer

PRATT AND LAMBERT

Product Identification

Product ID:24518-GREEN

MSDS Date:01/01/1985

FSC:8010

NIIN:00-530-5567

MSDS Number: BFDCF

Responsible Party

PRATT & LAMBERT

Emergency Phone: 316-733-1361

Cage: PRATT

Contractor

PRATT AND LAMBERT INC

2153

CLEVELAND, OH 44101-1027

US

216-566-2902

Cage: 61196

Ingredients

MINERAL SPIRITS

CAS: 64475-85-0

RTECS: PY8240000

Fraction By Weight: 35%

ACGIH TLV: 500 PPM

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight:

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TRIETHYLAMINE (SARA III)

CAS: 121-44-8

RTECS: YE0175000

Fraction By Weight:

OSHA PEL25 PPM/15 STEL

ACGIH TLV: 10 PPM/15 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ETHYL KETOXIME

RTECS: PM7783000

Hazards

Effects of Overexposure:IRRIT OF NOSE,THROAT,EYES & POSS DIZZINESS & NAUSEA.SPRAY MIST CONTN LEAD.

First Aid

First Aid:INHAL:REMOVE FR EXPOSUR & PROVID FRESH AIR.SPLASH EYES-FLUSH IMMED W/LG AMTS OF WATER FOR 15 MIN.SPLASH SKIN:REMOV CONTAM CLOTHING & WASH ALL AFFECT AREA W/WATR.INGEST:DO NOT INDUC VOMITNG.CONSULT A DR . IMMED IN ALL CASES.

Fire Fighting

Flash Point:104 F 40 C TCC

Extinguishing Media:CLASS B EXTING, CARBON DIOXIDE, DRY CHEM OR ALCOHOL FOAM

Fire Fighting Procedures:SELF CONTAINED BREATH APPARAT WATER MAY BE INEFFECTIVE.

Unusual Fire/Explosion Hazard:KEEP CONTNRS TIGHTHLY CLOS.ISOLAT FR HEAT,ELECTR EQPMT,SPARKS & OPN FLAME.DO NOT APPLY TO VRYHOT SUR

Accidental Release

Spill Release Procedures:REMOV ALL SOURCES OF IGNIT (FLAMES,HOT SURFACES,ELECTRICAL, STATIC OR FRICTIONAL SPARKS).VENTILAT AREA & AVOID BREATHING VAPORS.REMOV W/ INERT ABSORB & NON-SPARKING TOOLS.STEPS MUST BE TAKN TO PREVNT CONTAM OF GROUND WATR OR STREAMS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOV 120 F.STORE LG QUANTITIES IN COMPLIA W/OSHA 1910.106.CONTNRS SHLD BE GROUNDED & BONDED TO THE RECEIVING CONTNR.

Other Precautions:DO NOT CUT OR WELD ON EMPTY CONTAINER. DO NOT USE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER.

Exposure Controls

Respiratory Protection:NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY WHN SPRAYING IN OUTDR

Ventilation:PROVID GEN DILUT/LOC EXHAUST VENT TO KP CONCENT BELO ACEP TL

Protective Gloves:SOLVENT,IMPERME

Eye Protection:SAFETY EYEWR

Other Protective Equipment:PROTECTV EQPMT TO PRVNT SKN CONTCT.SE

OSHA,29 CFR 1910.1025

Supplemental Safety and Health

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:311-373

Vapor Density:>AIR

Evaporation Rate & Reference:Percent Volatiles by Volume:56

Stability

Stability Indicator/Materials to Avoid:YES

AVOID CONTCT W/STRONG ACIDS OR AKALINE MATERIALS.

Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES.

Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE & OXIDES OF CARBON & LEAD.

Conditions to Avoid Polymerization:DO NOT ADD DRIERS OR REACTIV CHEM W/O THEHN SUPERVISION.

Disposal

Waste Disposal Methods:DISPOSE IN ACCORD W/LOCAL, STATE & FEDERAL REGULATIONS.INCINERATIN EPA APPRVD FACILITY.DO NOT INCINERAT CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.