

## **ENAMEL ALKYD**

### **MSDS Number**

BFDCN

### **National Stock Number**

8010-00-530-5569

### **Product Name**

ENAMEL ALKYD

### **Manufacturer**

PRATT AND LAMBERT

### **Product Identification**

Product ID:ENAMEL ALKYD

MSDS Date:01/01/1985

FSC:8010

NIIN:00-530-5569

MSDS Number: BFDCN

### **Responsible Party**

PRATT & LAMBERT

Emergency Phone: 800-424-9300, NIGHT

Cage: PRATT

### **Contractor**

PRATT AND LAMBERT INC

206

KANSAS CITY, MO 64141

US

800-647-2253

Cage: 92216

### **Ingredients**

LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR

CAS: 7758-97-6

RTECS: GB2975000

Fraction By Weight:

OSHA PEL0.05 MG/M3 (PB)

ACGIH TLV: 0.05MG/M3(CR)A2;8990

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 40%

OSHA PEL100 PPM

LEAD NAPHTHENATE, 36%

RTECS: OG2025000

Fraction By Weight:

## Hazards

Effects of Overexposure:INH: RESP TRACT IRRIT, NERVOUS SYS DEPRESSANT, SKIN/EYE IRRIT.

## First Aid

First Aid:FLUSH EYES/SKIN W/WATER. REMOVE CONTAM CLOTHING. REMOVE TO FRESH AIR, CALL MD IF NEC.

## Fire Fighting

Flash Point:104F, 40C TCC

Lower Limits:1.10

Extinguishing Media:CO2, FOAM, DRY CHEM, POLYMER FOAM

Fire Fighting Procedures:SELF-CNTND BRTHNG APPARATUS. WATER, USE FOG NOZZ.

Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT, ELECTRICAL EQUIP, OPEN FLAME. CLOSED CNTNRS MAY EXPLODE WHEN VERY HOT.

## Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES. VENT AREA. REMOVE W/INERT ABSORBENT & NONSPARKING TOOLS.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F, 48.9C

Other Precautions:GROUND CNTNRS WHEN POURING AVOID EXCESS FREE FALL OF LIQ. DO NOT FLAMECUT, BRAZE, WELD W/O RESP & VENT. ADD LABEL WARNING. DO NOT TAKE INTERN.

## Exposure Controls

Respiratory Protection:OUTDOOR, USE MECH FILTER RESP. INDOOR, CHEM MECH.

Ventilation:GENERAL DILUTION OR LOCAL EXHST

Protective Gloves:REQ

Eye Protection:SPLASH GOGGLES

Other Protective Equipment:PREVENT PROLONGED SKIN CNTCT W/CONTAM CLOTHING

Supplemental Safety and Health

EMER DAY #316-733-1361. BOILING RANGE: 155-189.4C. RESP PROT: USE AIRLINE TYPE RESP IN CONFINED AREA.

## Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:311-373F

Vapor Pres:32

Evaporation Rate & Reference:Appearance and Odor:GREEN

Percent Volatiles by Volume:58.0

## Stability

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRES, HEAT, HOT SURFACES

## Disposal

Waste Disposal Methods:DISPOSE IAW LOCAL, STATE, FED REG. DO NOT INCINERATE CLOSED CNTNRS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.