
SCOTCHSEAL INDUSTRIAL SEALANT (3M EC 1063)

MSDS Number

BFDHW

National Stock Number

8030-00-537-7925

Product Name

SCOTCHSEAL INDUSTRIAL SEALANT (3M EC 1063)

Manufacturer

3M COMPANY ADHESIVE COATING AND SEALANT DIV

Product Identification

Product ID: SCOTCHSEAL INDUSTRIAL SEALANT (3M EC 1063)

MSDS Date: 01/01/1985

FSC: 8030

NIIN: 00-537-7925

MSDS Number: BFDHW

Responsible Party

3M COMPANY, ADHESIVE COATING & SEALANT DIV.

3M CENTER

ST. PAUL, MN 55144-1000

US

Emergency Phone: 612-733-1110

Info Phone: 612-733-1110

Cage: 04963

Contractor

3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

SAINT PAUL, MN 55144-1000

US

800-364-3577/651-737-6501(24 HOURS)

Cage: 04963

Ingredients

LEAD PEROXIDE (LEAD DIOXIDE), (OSHA PEL FROM 29CFR

CAS: 1309-60-0

RTECS: OG0700000

Fraction By Weight: 50%.

OSHA PEL 0.05 MG/M3 (PB)

ACGIH TLV: 0.15 MG/M3(PB); 8990

DIBUTYL PHTHALATE (SARA III)

CAS: 84-74-2

RTECS: TI0875000

OSHA PEL 5 MG/M3

ACGIH TLV: 5 MG/M3; 9192

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

STEARIC ACID (COMBINED W/DIBUTYL PHTHALATE.COMPRISES

CAS: 57-11-4

RTECS: WI2800000

Hazards

Effects of Overexposure:CHRONIC EXPOSURE CAN LEAD TO LEAD POISONING.
AVOID EYE & SKIN CONTACT.

First Aid

First Aid:EYE: FLUSH W/ PLENTY OF WATER & CALL A PHYSICIAN.

Fire Fighting

Extinguishing Media:CO*2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:COLLECT SPILLED MATERIAL USING ABSORBENT
MATERIAL. CLEAN UP RESIDUE & AREA.

Handling

Handling and Storage Precautions:AVOID EYE CONTACT 6 PROLONGED SKIN
CONTACT. WASH HANDS BEFORE EATING OR SMOKING. LAUNDRY CONTAMINATED
CLOTHING BEFORE REUSE.

Exposure Controls

Ventilation:MFR STATES: MECHANICAL VENTILATION ADEQUATE

Protective Gloves:IMPERV. GLOVES

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

SOLUBILITY IN WATER: VERY SLIGHT, THIS PRODUCT CAN BE USED W/EC-801
(ADHESIVE). KEY1: J3.

Chemical Properties

HCC:D1

Spec Gravity:1.9

Appearance and Odor:DARK BROWN PASTE

Percent Volatiles by Volume:0.0

Stability

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO, CO*2, & SMOKE PARTICLES

Disposal

Waste Disposal Methods:MFR RECM: LG QTY--DISPOSE IN SECURE LANDFILL AT
HAZARDOUS WASTE MANAGEMENT FACILITY. CONSULT APPROPRIATE FED.,
STATE & LOCAL CODES. SM QTY--DISPOSE OF INDIV EMPTY CONTAINERS IN A
SANITARY LANDFILL IAW FED,. STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.