

## **226C,COMPOUND THINNING LIQUID.**

### **MSDS Number**

BFDNJ

### **National Stock Number**

8010-00-543-4036

### **Product Name**

226C,COMPOUND THINNING LIQUID.

### **Manufacturer**

SEAPORT CHEMICALS CO

### **Product Identification**

Product ID:226C,COMPOUND THINNING LIQUID.

MSDS Date:01/01/1985

FSC:8010

NIIN:00-543-4036

MSDS Number: BFDNJ

### **Responsible Party**

SEAPORT CHEMICALS CO

610 DEXTER AVE N

SEATTLE , WA 98109

US

Cage: 2E758

### **Contractor**

SEAPORT CHEMICALS CO

SEATTLE, WA 98109

US

Cage: 2E758

### **Ingredients**

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

N-BUTYL ACETATE (SARA III)

CAS: 123-86-4

RTECS: AF7350000

OSHA PEL150 PPM/200 STEL

ACGIH TLV: 150 PPM/200STEL;9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOBUTYL ACETATE

ACGIH TLV: 150 PPM

## Hazards

Effects of Overexposure:EYE/SKIN: IRRIT. VAPORS: DIZZY,HEADACHE,SLIGHT EUPHORIA,LOSS OF COORDINATION,LOGHT-HEADED FEELING.

## First Aid

First Aid:EYE: FLUSH WITH WATER 15 MIN. SKIN: FLUSH WITH WATER.  
INHALATION: REMOVE TO FRESH AIR. INGESTION: DO NOT INDUCE  
VOMITING,CALL PHYSICIAN

## Fire Fighting

Flash Point:Lower Limits:1.5  
Upper Limits:11  
Extinguishing Media:CO2,DRY CHEMICAL,FOAM  
Fire Fighting Procedures:SELF-CONTAINED BREATH APP  
Unusual Fire/Explosion Hazard:FLAMES MAY BE DIFFICULT TO SEE (BLUE  
FLAME)

## Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION IN VICINITY  
OF SPILL,VENTILATE WELL TO RELEASE VAPORS,CLEAN UP AS SOON AS  
POSSIBLE.

## Handling

Handling and Storage Precautions:KEEP AWAY FROM OPEN FLAME,USE IN WELL  
VENTILATED AREA. AVOID CONTACT WITH SKIN OR EYES  
Other Precautions:DANGER - HARMFUL OR FATAL IF SWALLOWED.

## Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH  
EXPOSURE OF CONCERN.  
Ventilation:LOCAL/MECHANICAL,EXPLOSION PROOF MOTORS.  
Protective Gloves:NEOPRENE/RUBBER  
Eye Protection:GOGGLES  
Other Protective Equipment:AS REQUIRED TO PREVENT SKIN CONTACT.  
Supplemental Safety and Health  
ADD INGRED: METHYL ETHYL KETONE,TLV 200PPM; ISOPROPYL ALCOHOL,TLV  
400PPM; SO 250,TLV 250PPM(MFR). PKG: 2 OZ BOTTLE

---

## Chemical Properties

HCC:F2  
Boiling Pt:B.P. Text:176F/80C  
Vapor Pres:19  
Vapor Density:3.3  
Spec Gravity:0.815  
Evaporation Rate & Reference:1.53  
Solubility in Water:APPRECIABLE  
Appearance and Odor:COLORLESS LIQUID,KETONE/ALCOHOL SMELL  
Percent Volatiles by Volume:>99

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Hazardous Decomposition Products:CO\*2,WATER

## Disposal

Waste Disposal Methods:FLUSH WELL WITH WATER,FLUSH DRAIN WITH WATER TO  
AVOID VAPOR BACK-UP. COMPLY WITH ALL LOCAL,STATE AND FEDERAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.