https://msdsreport.com/msds/BFFLN

# PR-1005-L-R

**MSDS Number** 

BFFLN

**National Stock Number** 

# 8030-00-559-7532

Product Name

PR-1005-L-R

Manufacturer PRODUCTS RESEARCH AND CHEMICAL CORP

## **Product Identification**

Product ID:PR-1005-L-R MSDS Date:01/01/1985 FSC:8030 NIIN:00-559-7532 MSDS Number: BFFLN

# **Responsible Party**

PRODUCTS RESEARCH & CHEMICAL CORPORATION

5430 SAN FERNANDO ROAD

GLENDALE, CA 91209

US

Emergency Phone: 818-240-2060

Info Phone: 818-240-2060

Cage: DO563

## Contractor

PRODUCTS RESEARCH & CHEMICAL

1800

GLENDALE, CA 91209

US

818-240-2060

Cage: DO563

## Ingredients

ISOPROPYL ALCOHOL (SARA III) CAS: 67-63-0 RTECS: NT8050000 Fraction By Weight: 15.0% OSHA PEL400 PPM/500 STEL ACGIH TLV: 400 PPM/500STEL;9192

PHENOLIC RESIN Fraction By Weight: 10.0% ACGIH TLV: UNK

# msds report

#### https://msdsreport.com/msds/BFFLN

•

CAS: 108-10-1 RTECS: SA9275000 Fraction By Weight: 10.0% OSHA PEL100 PPM/75 STEL ACGIH TLV: 50 PPM/75 STEL; 9293 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS: 78-93-3 RTECS: EL6475000 Fraction By Weight: 55.0% OSHA PEL200 PPM/300 STEL ACGIH TLV: 200 PPM/300STEL 9192 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

#### Hazards

Effects of Overexposure: IRRITATION OF EYES AND RESPIRATORY TRACT.

#### **First Aid**

First Aid:SKIN:WASH THOROUGHLY WITH SOAP & WATER.EYES:WASH OUT WITH PLENTY OF WATER;SEE A DR.INHALATION:REMOVE TO FRESH AIR.

#### **Fire Fighting**

Flash Point:>23F(PMCC) Lower Limits:1.8 Upper Limits:10.0 Extinguishing Media:DRY CHEMICAL,FOAM,CO\*2 Fire Fighting Procedures:ALCOHOL FOAM

#### **Accidental Release**

Spill Release Procedures: VENTILATE AREA.REMOVE ALL SOURCES OF IGNITION.WEAR RUBBER GLOVES & MOP UP WITH USE RAGS OR PAPER TOWELS.

#### Handling

Handling and Storage Precautions: INSIDE STORAGE IN STANDARD FLAME-RESISTANT FLAMMABLE LIQUIDS STORAGE ROOM OR CABINET.

#### **Exposure Controls**

Respiratory Protection:NIOSH ORGANIC VAPOR CARTRIDGE RESPIRATOR OR AIRLINE RESPIRATOR. Ventilation:LOCAL EXHAUST ADEQUATE TO MINIMIZE VAPORS.MECHANICAL Protective Gloves:RUBBER Eye Protection:CHEMICAL GOGGLES. Supplemental Safety and Health

#### **Chemical Properties**

HCC:F2 Boiling Pt:B.P. Text:175 F Vapor Pres:71 Vapor Density:2.54 Spec Gravity:0.84 Evaporation Rate & Reference:>1,BUTYL ACETATE Solubility in Water:SLIGHT Appearance and Odor:THIN,RED SYRUP;KETONE ODOR Percent Volatiles by Volume:83.0

# Stability

Stability Indicator/Materials to Avoid:YES Hazardous Decomposition Products:CO,CO\*2

#### Disposal

Waste Disposal Methods:LANDFILL UNLESS PROHIBITED BY LAW.OTHERWISE,INCINERATE.DO NOT INCINERATE SEALED CONTAINERS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.