

TT-E-508,ENAMEL,SYNTHETIC

MSDS Number

BFGBT

National Stock Number

8010-00-579-9200

Product Name

TT-E-508,ENAMEL,SYNTHETIC

Manufacturer

TRIAD PAINT AND CHEMICAL CORP

Product Identification

Product ID:TT-E-508,ENAMEL,SYNTHETIC

MSDS Date:01/01/1985

FSC:8010

NIIN:00-579-9200

MSDS Number: BFGBT

Responsible Party

TRIAD PAINT & CHEMICAL CORP.

810 EVERGREEN AVE

BROOKLYN , NY 11207-1140

US

Cage: JO907

Contractor

TRIAD PAINT AND CHEMICAL CORP

BROOKLYN, NY 11207-1140

US

(718) 443-2278

Cage: 33151

Ingredients

SOLVENTS

Fraction By Weight: 25.0%

ACGIH TLV: 200PPM

Hazards

Effects of

Overexposure:ANESTHESIA,HEADACHE,NAUSEA,DIZZINESS,ETC.LIQUID-MILDLY
TO MODERATELY EYE IRRITATING

First Aid

First Aid:REMOVE VICTIM AND RESTORE BREATHING IF NECESSARY.WASH SKIN
WITH SOAP AND WATER.FLUSH EYES WITH COLD WATER.

Fire Fighting

Flash Point:105 F, 41C TCC

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:DRY CHEMICAL,FOAM,CO*2,STEAM,WATER FOG,

Fire Fighting Procedures:DO NOT USE WATER.EXCLUDE AIR.CONSULT FIRE
MARSHALL

Unusual Fire/Explosion Hazard:VAPOR FORMS EXPLOSIVE MIXTURE BETWEEN
UPPER AND LOWER EXPLOSIVE UNITS.

Accidental Release

Spill Release Procedures:AVOID FLAME AND SPARK SOURCES.PROVIDE ADEQUATE VENTILATION.

Handling

Handling and Storage Precautions:AVOID OPEN FLAME AND SPARK SOURCES.AVOID SPLASH FILLING.PROVIDE ADEQUATE VENTILATION.AVOID EXCESSIVE HEAT

Exposure Controls

Respiratory Protection:ORGANIC CANNISTER MASK OR AIR PACK
Ventilation:APPROVED CLASS D EXPLOSION PROOF MOTOR AND SWITCHES.
Protective Gloves:SOLVENT RESIST.
Eye Protection:CONVENTIONAL EYE COVER
Other Protective Equipment:NA
Supplemental Safety and Health
BOILING RANGE 157-194C.

Chemical Properties

Boiling Pt:B.P. Text:315-382F
Vapor Density:5.0
Spec Gravity:0.78
Evaporation Rate & Reference:BUTYL ACETATE 0.13
Solubility in Water:NEGLIGIBLE
Appearance and Odor:YELLOW PAINT,HYDROCARBON ODOR
Percent Volatiles by Volume:45.0

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CO, CO*2 WHEN COMBUSTED

Disposal

Waste Disposal Methods:EVAPORATE OR FLUSH WITH WATER IN A WELL VENTILATED AREA.USE OIL SEWER IF AVAILABLE,OR REMOVE TO A CONTAINER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.