X-3917 ZINC CHROMATE PRIMER

MSDS Number

BFGGG

National Stock Number

8010-00-582-5318

Product Name

X-3917 ZINC CHROMATE PRIMER

Manufacturer

SENTRY PAINT AND CHEMICAL CO DARBY PA 19023

Product Identification

Product ID:X-3917 ZINC CHROMATE PRIMER
MSDS Date:01/01/1985
FSC:8010
NIIN:00-582-5318
MSDS Number: BFGGG

Responsible Party

SENTRY PAINT & CHEMICAL CO, DARBY, PA 19023

Emergency Phone: 215-GL9-5320

Cage: GO855

Contractor

SENTRY PAINT AND CHEMICAL CO

DARBY, PA 19023

US

Cage: 34346

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ZINC CHROMATE

CAS: 13530-65-9

RTECS: GB3290000

OSHA PEL0.1 MG/M3 (CRO3)

ACGIH TLV: 0.01MG/M3(CR)A1;9192

ALKYD

PHENOLIC

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

OSHA PEL100 PPM

Hazards

Effects of Overexposure:DIZZINESS, HEADACHE AND NAUSEA

First Aid

First Aid:REMOVE TO RESH AIR. GIVE ARTIFICIAL RESPIRATION IF BREATHING STOPS.

Fire Fighting

Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:FOAM,CO2,DRY CHEMICAL
Fire Fighting Procedures:USE EQUIPMENTSUPPLIED AIR SUPPLY FOR ENCLOSED AREAS.
Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID

Accidental Release

Spill Release Procedures:CLEAN UP AS ANY FLAMMABLE LIQUID. AVOID SPARKS, USE DRY ABSORBENT IF POSSIBLE

Handling

Handling and Storage Precautions:AVOID OPEN FLAME AND HIGH TEMPERATURE

Exposure Controls

Respiratory Protection:CARTRIDGE TYPE RESPIRATOR
Ventilation:LOCAL EXHAUST
Supplemental Safety and Health
TALC----- IPALC/HEPTUNE

Chemical Properties

HCC:F3
Boiling Pt:B.P. Text:240F
Vapor Pres:36
Vapor Density:3.9
Spec Gravity:1.2
Evaporation Rate & Reference:FASTER THAN NBUACT
Solubility in Water:NONE
Appearance and Odor:GREEN PRIMER
Percent Volatiles by Volume:63.0

Stability

Stability Indicator/Materials to Avoid:YES

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.