

YELLOW #13578

MSDS Number

BFGLC

National Stock Number

8010-00-584-3082

Product Name

YELLOW #13578

Manufacturer

AMERON INDUSTRIAL COATINGS DIV

Product Identification

Product ID:YELLOW #13578 MSDS Date:01/01/1987 FSC:8010 NIIN:00-584-3082 MSDS Number: BFGLC

Responsible Party

AMERON INDUSTRIAL COATINGS DIVISION

201 N BERRY ST

BREA, CA 92621-3904

US

Emergency Phone: 714-529-4597

Info Phone: 714-529-4597

Cage: 09869

Contractor

AMERON INDUSTRIAL COATINGS DIVISION

BREA, CA 92621-3904

714-529-4597

US

Cage: 09869

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6 RTECS: SE7555000

Fraction By Weight: 44.6%

OSHA PEL100 PPM

Hazards

Effects of Overexposure: ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

First Aid

First Aid: IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A PHYSICIAN IF CONDITIONS PERSIST.

Fire Fighting

Flash Point:85F TCC



Lower Limits: 1.1

Extinguishing Media: SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LAGE

FIRES-FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING

Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.

Other Precautions: CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FAL OF LIQUID IN EXCESS OF A FEW INCHES

Exposure Controls

Respiratory Protection: USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation: PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY

Supplemental Safety and Health

RESPIRATOR USE BASED ON CHEM. CONC. AND CONDITIONS OF USE.

Chemical Properties

HCC:F3

Boiling Pt:B.P. Text:311-373F

Vapor Density:>1

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume:61.0

Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:AVOID FIRE,HEAT AND HOT SURFACES

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.