

YELLOW #13711

MSDS Number

BFGLM

National Stock Number

8010-00-584-3092

Product Name

YELLOW #13711

Manufacturer

AMERON INDUSTRIAL COATINGS DIV

Product Identification

Product ID:YELLOW #13711

MSDS Date:01/01/1987

FSC:8010

NIIN:00-584-3092

MSDS Number: BFGLM

Responsible Party

AMERON INDUSTRIAL COATINGS DIVISION

Emergency Phone: 316-733-1361

Cage: 09869

Contractor

AMERON INDUSTRIAL COATINGS DIVISION

BREA, CA 92621-3904

US

714-529-4597

Cage: 09869

Ingredients

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight:

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000

Fraction By Weight: 12.0%

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight:

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

ETHYL BENZENE (SARA III)

CAS: 100-41-4

RTECS: DA0700000

Fraction By Weight:

OSHA PEL100 PPM/125 STEL

ACGIH TLV: 100 PPM/125STEL 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

First Aid

First Aid:IN CASE OF CONTACT-FLUSH SKIN AND EYES WITH WATER AND REMOVE CONTAMINATED CLOTHING. IF INHALED-REMOVE TO FRESH AIR. CALL A PHYSICIAN IF CONDITIONS PERSIST.

Fire Fighting

Flash Point:28F TCC

Lower Limits:0.9

Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE FIRES-FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE

QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.

Other Precautions: CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE-FALL OF LIQUID IN EXCESS OF A FEW INCHES.

Exposure Controls

Respiratory Protection: USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation: PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY

Supplemental Safety and Health

NT8050000 ISOPROPYL ALCOHOL EL6475000 METHYL ETHYL KETONE RESPIRATOR USE BASED ON CHEM CONC. AND CONDITIONS OF USE.

Chemical Properties

HCC:F3

Boiling Pt: B.P. Text: 175-329F

Vapor Density: >1

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 87.7

Stability

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: AVOID FIRE, HEAT AND HOT SURFACES

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.