

# **YELLOW #13594**

# **MSDS Number**

**BFHDB** 

# **National Stock Number**

8010-00-597-8229

### **Product Name**

YELLOW #13594

#### Manufacturer

AMERON INDUSTRIAL COATINGS DIV

### **Product Identification**

Product ID:YELLOW #13594 MSDS Date:01/01/1987 FSC:8010 NIIN:00-597-8229 MSDS Number: BFHDB

# **Responsible Party**

AMERON INDUSTRIAL COATINGS DIVISION

201 N BERRY ST

BREA, CA 92621-3904

US

Emergency Phone: 714-529-4597

Info Phone: 714-529-4597

Cage: 09869

Contractor

AMERON INDUSTRIAL COATINGS DIVISION

BREA, CA 92621-3904

714-529-4597

US

Cage: 09869

# **Ingredients**

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6 RTECS: SE7555000

Fraction By Weight: 41.6%

OSHA PEL100 PPM

LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR

CAS: 7758-97-6 RTECS: GB2975000 Fraction By Weight: 0.5%

OSHA PEL0.05 MG/M3 (PB)

ACGIH TLV: 0.05MG/M3(CR)A2;8990

**Hazards** 



Effects of Overexposure: ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

#### First Aid

First Aid:IN CASE OF CONTACT-FLUSH SKIN AND EYES WITH WATER AND REMOVE CONTAMINATED CLOTHING. IF INHALED-REMOVE TO FRESH AIR. CALL A PHYSICIAN IF CONDITIONS PERSIST.

# Fire Fighting

Flash Point:85F TCC Lower Limits:1.1

Extinguishing Media: SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE

FIRES-FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE

#### **Accidental Release**

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE INERT ABSORBENT AND NON-SPARKING TOOLS.

# Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.

Other Precautions: CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE-FALL OF LIOUID IN EXCESS OF A FEW INCHES.

# **Exposure Controls**

Respiratory Protection: USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation: PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY Supplemental Safety and Health

RESPIRATOR USE BASED ON CHEM CONC. AND CONDITION OF USE.

### **Chemical Properties**

HCC:F3

Boiling Pt:B.P. Text:311-373F

Vapor Density:>1

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 60.1

### Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:AVOID FIRE, HEAT AND HOT SURFACES

# Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.