

10080-BROWN

MSDS Number

BFHHN

National Stock Number

8010-00-598-5470

Product Name

10080-BROWN

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID:10080-BROWN MSDS Date:01/01/1985 FSC:8010 NIIN:00-598-5470 MSDS Number: BFHHN

Responsible Party

PRATT AND LAMBERT INC

16116 E 13TH ST

WICHITA, KS 67201

US

Emergency Phone: 716-873-6000 DOT EMER 8002553924

Info Phone: 316-733-1361

Cage: 61196

Contractor

PRATT AND LAMBERT INC

6027

CLEVELAND, OH 44101-1027

US

216-566-2902 Cage: 61196

Ingredients

MINERAL SPIRITS CAS: 64475-85-0 RTECS: PY8240000

Fraction By Weight: 45.0%

ACGIH TLV: 500 PPM

METHYL ETHYL KETOXIME

RTECS: PM7783000 Fraction By Weight:

TRIETHYLAMINE (SARA III)

CAS: 121-44-8 RTECS: YE0175000



Fraction By Weight:

OSHA PEL25 PPM/15 STEL

ACGIH TLV: 10 PPM/15 STEL; 9293 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS: NP9625000 Fraction By Weight: OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293
EPA Report Quantity: 5000 LBS
DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure: IRRIT OF NOSE, THROAT, EYES & POSS DIZZINESS & NAUSEA. SPRAY MIST CONTN LEAD.

First Aid

First Aid:INHAL:REMOVE FR EXPOSR & PROVID FRESH AIR.SPLASH EYES-FLUSH IMMED W/LG AMTS OF WATER FOR 15 MIN.SPLASH SKIN:REMOV CONTAM CLOTHING & WASH ALL AFFECT AREA W/WATR.INGEST:DO NOT INDUC VOMITING.CONSULT A D R. IMMED IN ALL CASES.

Fire Fighting

Flash Point: 104F 40C TCC

Extinguishing Media:CLASS B EXTING, CARBON DIOXIDE, DRY CHEM OR ALCOHOL FOAM

Fire Fighting Procedures: SELF CONTAINED BREATH APPARAT. WATER MAY BE

INEFFECTIVE.

Unusual Fire/Explosion Hazard: KEEP CONTNRS TIGHTLY CLOS.ISOLAT FR HEAT, ELECTR EQPMT, SPARKS & OPN FLAME. DO NOT APPLY TO VRY HOT SUR

Accidental Release

Spill Release Procedures: REMOV ALL SOURCES OF IGNIT (FLAMES, HOT SURFACES, ELECTRICAL, STATIC OR FRICTIONAL SPARKS). VENTILAT AREA & AVOID BREATHING VAPORS. REMOV W/ INERT ABSORB & NON-SPARKING TOOLS. STEPS MUST BE TAKN TO PREVNT C ONTAM OF GROUND WATR OR STREAMS.

Handling

Handling and Storage Precautions: DO NOT STORE ABOV 120F.STORE LG QUANTITIES IN COMPLIA W/OSHA 1910.106.CONTNRS SHLD BE GROUNDED & BONDED TO THE RECEIVING CONTNR.

Other Precautions: DO NOT CUT OR WELD ON EMPTY CONTAINER. DO NOT USE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER.

Exposure Controls

Respiratory Protection:NIOSH APPRVD MECH RESPIRAT TO REMOV OVERSPRAY

WHN SPRAYING IN OUTDR

Ventilation: PROVID GEN DILUT/LOC EXHAUST VENT TO KP CONCENT BELO ACEP

TL

Protective Gloves: SOLVENT, IMPERME

Eye Protection: SAFETY EYEWR

Other Protective Equipment: PROTECTV EQPNT TO PRVNT SKN CONTCT.SE OSHA

29 CFR 1910.1025



Supplemental Safety and Health

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:311-373F

Vapor Density:>AIR

Evaporation Rate & Reference: Percent Volatiles by Volume: 62

Stability

Stability Indicator/Materials to Avoid:YES
AVOID CONTCT W/STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid:FIRES,HEAT & HOT SURFACES.
Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE & OXIDES OF CARBON & LEAD.
Conditions to Avoid Polymerization:DO NOT ADD DRIERS OR REACTIV CHEM W/O TECHN SUPERVISION.

Disposal

Waste Disposal Methods: DISPOSE IN ACCORD W/LOCAL, STATE & FEDERAL REGULATIONS. INCINERAT IN EPA APPRVD FACILITY. DO NOT INCINERAT CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.