

TT-E-508C

MSDS Number

BFHYN

National Stock Number

8010-00-616-0008

Product Name

TT-E-508C

Manufacturer

DURON INC

Product Identification

Product ID:TT-E-508C
MSDS Date:01/01/1987
FSC:8010
NIIN:00-616-0008
MSDS Number: BFHYN

Responsible Party

DURON, INC.
10406 TUCKER ST
BELTSVILLE , MD 20705-2201
US
Cage: LO183

Contractor

DURON, INC.
BELTSVILLE, MD 20705-4600
US
301-937-4600
Cage: LO183

Ingredients

TITANIUM DIOXIDE SILICATES CALCIUM CARBONATE
Fraction By Weight: 46.6%

ALKYD RESIN (SOLIDS)

MINERAL SPIRITS (EXEMPT)
CAS: 64475-85-0
RTECS: PY8240000
Fraction By Weight: 28.9%

DRIERS
Fraction By Weight: 0.3%

Hazards

Effects of Overexposure:IRRIT OF RESPIRATOR TRACT & EYES.INHAL OF HIGH
VAP CAONCENTR.MAY HAVE RESULTS RANGING FR DIZZINESS &

First Aid

First Aid:EYES-FLUSH FOR 15 MIN-GET MEDICAL ATTN.IF OVERCOME BY VAPOR, REMOVE FROM EXPOSED AREA. IF BREATHING IR IRREGULAR OR STOPPED,START RESUSCITATION.

Fire Fighting

Flash Point:104 F TCC 40 C
Lower Limits:0.9
Extinguishing Media:USE CARBON DIOXIDE,DRY CHEMICAL OR FOAM
Fire Fighting Procedures:FIGHT LIKE A GASOLINE FLASH FIRE
Unusual Fire/Explosion Hazard:EXPOSURE TO EXTREME HEAT MAY CAUSE BURSTING OF CLOSED CONTAINERS

Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES,KEEP PEOPLE AWAY.RECOVER LIQUID ADD ABSORBENT TO SPILL AREA.AVOID BREATHING VAPORS. VENTILATE ENCLOSED SPACES.KEEP PETROLEUM PRODUCTS OUT OF ALL PUBLIC SEWER & STREAM.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.
Other Precautions:AVOID PROLONGED CONTACT W/SKIN.DO NOT TAKE INTERNALLY.

Exposure Controls

Respiratory Protection:HYDROCARBON OR ORGANIC VAP CANISTERS.SELF CONTAIN APPARATUS ABOV TLV
Ventilation:LOCAL EXH-FACE VELOCITY 60 FPM
Protective Gloves:RBBR OR PLASTIC
Eye Protection:SAFETY GOGGLES OR GLASSES
Other Protective Equipment:MUST COMPLY W/SECTION 1910,142.135 OSHA STDS
Supplemental Safety and Health

Chemical Properties

HCC:F4
Vapor Density:HEAV
Spec Gravity:1.327
Percent Volatiles by Volume:49.3

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:STRONG OXIDANTS LIKE LIQ CHLORINAE & CONCENTR OXYG HIGH TEMP
Hazardous Decomposition Products:CARBON MONOXIDE IN THE CASE OF INCOMPLETE COMBUSTION

Disposal

Waste Disposal Methods:PLACE IN CLOSED DOT APPROVED CONTAINER.RAGS & ABSORBENT MATERIAL SHD BE IMMEDIATELY IMMERSED IN WATER.USE APPRVED LANDFILL IN ACCORDANCE W/LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.