

## **TT-E-508C**

### **MSDS Number**

BFHXP

### **National Stock Number**

8010-00-616-0009

### **Product Name**

TT-E-508C

### **Manufacturer**

DURON INC

### **Product Identification**

Product ID:TT-E-508C  
MSDS Date:01/01/1987  
FSC:8010  
NIIN:00-616-0009  
MSDS Number: BFHXP

### **Responsible Party**

DURON,INC  
10406 TUCKER ST  
BELTSVILLE , MD 20705-2201  
US  
Cage: HO323

### **Contractor**

DURON,INC  
BELTSVILLE, MD 20705  
US  
301-937-4600  
Cage: HO323

### **Ingredients**

YELLOW-IRON OXIDE  
RTECS: ZF8280000

TITANIUM DIOXIDES SILICATES CALCIUM CARBONATE.

ALKYD RESIN (SOLIDS)

MINERAL SPIRITS (EXEMPT)  
CAS: 64475-85-0  
RTECS: PY8240000

DRIERS  
Fraction By Weight: 0.3%

### **Hazards**

Effects of Overexposure:IRRIT OF RESPIRATORY TRACT & EYES.INHAL OF HIGH VAP CONCENTR MAY HAVE RESLTS RANGING FR DIZZ & HEADA

## First Aid

First Aid:EYES-FLUSH W/WATER FOR 15 MIN-GET MEDICAL ATTENTION. IF OVERCOME BY VAPORS, REMOVE FROM EXPOSED AREA. IF BREATHING IS IRREGULAR OR STOPPED, START RESUSCITATION.

## Fire Fighting

Flash Point:104 F TCC 40 C  
Extinguishing Media:USE CARBON DIOXIDE, DRY CHEMICAL OR FOAM  
Fire Fighting Procedures:FIGHT LIKE A GASOLINE FLASH FIRE.  
Unusual Fire/Explosion Hazard:EXPOSURE TO EXTREME HEAT MAY CAUSE BURSTING OF CLOSED CONTAINER

## Accidental Release

Spill Release Procedures:REMOVE ALL IGNITION SOURCES,KEEP PEOPLE AWAY. RECOVER LIQ ADD ABSORBENT TO SPILL AREA. AVOID BREATHING VAPORS. VENTILATE ENCL SPACES.KEEP PETROLEUM PRODUCTS OUT OF ALL PUBLIC SEWER & STREAM.

## Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS,AND OPEN FLAME.  
Other Precautions:AVOID PROLONGED CONTACT W/SKIN.DO NOT TAKE INTERNALLY.

## Exposure Controls

Respiratory Protection:HYDROCARBON OR ORGANIC VAP CANISTERS.SELF-CNTND APPARAT ABOVE TLV.  
Ventilation:FACE VELOCITY 60 FPM-LOCAL EXHAUST)  
Protective Gloves:RBBR/OR PLASTIC  
Eye Protection:SAFETY GOGGLES OR GLASSES  
Other Protective Equipment:MUST COMPLY W/SECTION 1910,132-;.135 OSHA STDS  
Supplemental Safety and Health

## Chemical Properties

HCC:F4  
Vapor Density:HEAV  
Spec Gravity:1.309  
Appearance and Odor:LIQUID PAINT-MILD ODOR  
Percent Volatiles by Volume:47.2

## Stability

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:STRONG OXIDANTS LIKE LIQ. CHLORINE & CONCENTRA OXYGEN HIGH T  
Hazardous Decomposition Products:CARBON MONOXIDE IN THE CASE OF INCOMPLETE COMBUSTION.

## Disposal

Waste Disposal Methods:PLACE IN CLOSED DOT APPROVED CONTAINER. RAGS & ABSORBENT MATERIAL SHD BE IMMEDIATELY IMMERSED IN WATER.USE APPROVED LANDFILL IN ACCORDANCE W/LOCAL STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.